



BURNDY Catalog Number
UPC Number
Description
Status

YA26L
 7818101438277
 COPPER HYLUG BULK PACKAG
 Active

Web Use
 BURNDY Product Line

Tongue Angle
 Length (in)
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 Strip Length

Dimensional

Straight
 2.19
 Chamfered,Skived
 0.39
 Standard
 0.12
 0.94
 0.83
 1

Number of Holes

General

1
 Cu Comp Terminal Code Cond, Bvl
 Entry, 1 Hole/W/InspWindow, 2/0
 AWG Str Code, 125 Navy, 600 V-
 35 kV, 3/8" Stud, Std bbl, Black,
 13 Index

Product Description

Conductor(s)

Flex (Class G) Size - Range
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Copper Solid Size (Range)
 DLO Size (Range)
 Copper Stranded (Range)

N/A
 N/A
 N/A
 N/A
 N/A
 2/0 AWG

Type of Plating
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Physical

Tin - Electro Plated
 Black
 Y
 13
 Copper

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS
 Industry Standards

Approvals / Certifications

Y
 Y
 Compliant
 N
 N
 UL467

Documentation

For further technical assistance, please contact us