



## On Line Catalog



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YA282TC38  
 7818108212511  
 CU HYDENT-4/0AWG-(2) 3/8  
 Active

**Web Use**  
 BURNDY Product Line

### Dimensional

Tongue Angle Straight  
 Length (in) 3.99  
 Tongue Type Standard  
 Barrell Style Chamfered  
 Bolt Hole Size (in) 0.39  
 Barrel Type Long  
 Thickness 0.14  
 B Length (in) 1.62  
 Pad Width (in) 1.02  
 E - in 1.00  
 Strip Length 1-11/16

### General

Number of Holes 2  
 Product Description Copper Compression lug, 2 Hole w/o Inspection Window, 4/0 AWG, 3/8" Stud, 1" Stud hole spacing, Long Barrel, Tin Plated

### Conductor(s)

Flex (Class G) Size - Range N/A  
 Flex (Class H) Size - Range N/A  
 Flex (Class I) Size - Range N/A  
 Copper Solid Size (Range) 4/0 AWG  
 DLO Size (Range) N/A  
 Copper Stranded (Range) 4/0 AWG


### Physical

Type of Plating Tin - Electro Plated  
 Bolt Hole Size 3/8  
 Color Code Purple  
 Plated (Yes or No) Y  
 Index Number 15  
 Product Material Copper

### Approvals / Certifications

UL Listed Y  
 CSA Certified Y  
 ROHS Compatible Compliant  
 UL Recognized N  
 CULUS N  
 Industry Standards UL468A-468B

### Documentation



For further technical assistance, please contact us