



BURNDY Catalog Number YA292TC38
UPC Number 7818100181255
Description 250MCM 2-H 3/8STUD
Status Active

Web Use
 BURNDY Product Line

Dimensional
 Tongue Angle Straight
 Length (in) 4.02
 Tongue Type Standard
 Barrell Style Chamfered
 Bolt Hole Size (in) 0.39
 Barrel Type Long
 Thickness 0.16
 B Length (in) 1.62
 Pad Width (in) 1.10
 E - in 1.00
 Strip Length 1-11/16

Number of Holes 2

General
 Product Description Copper Compression lug, 2 Hole w/o Inspection Window, 250 kcmil, 3/8" Stud, 1" stud hole spacing, Long Barrel, Tin Plated

Conductor(s)
 Flex (Class G) Size - Range N/A
 Flex (Class H) Size - Range N/A
 Flex (Class I) Size - Range N/A
 Copper Solid Size (Range) 250
 DLO Size (Range) N/A
 Copper Stranded (Range) 250

Physical
 Type of Plating Tin - Electro Plated
 Bolt Hole Size 3/8
 Color Code Yellow
 Plated (Yes or No) Y
 Index Number 16
 Product Material Copper

Approvals / Certifications
 UL Listed Y
 CSA Certified Y
 ROHS Compatible Compliant
 UL Recognized N
 CULUS N
 Industry Standards UL468A-468B

Documentation

For further technical assistance, please contact us