



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YA29L4  
 7818105545244  
 250 CU 1-HOLE SHORT 3/8  
 Active

**Web Use**  
 BURNDY Product Line

Tongue Angle  
 Length (in)  
 Tongue Type  
 Barrell Style  
 Bolt Hole Size (in)  
 Barrel Type  
 Thickness  
 B Length (in)  
 Pad Width (in)  
 Strip Length

**Dimensional**

Straight  
 2.42  
 Standard  
 Chamfered,Skived  
 0.39  
 Standard  
 0.16  
 1.06  
 1.11  
 1-1/8

Number of Holes  
 Product Description

**General**

1  
 Copper Compression Lug, 1 Hole  
 w/ Inspection Window, 250 kcmil,  
 3/8" Stud, Short Barrel, Tin Plated

Flex (Class G) Size - Range  
 Flex (Class H) Size - Range  
 Flex (Class I) Size - Range  
 Copper Solid Size (Range)  
 DLO Size (Range)  
 Copper Stranded (Range)

**Conductor(s)**

N/A  
 N/A  
 N/A  
 N/A  
 N/A  
 250 kcmil

Type of Plating  
 Color Code  
 Plated (Yes or No)  
 Index Number  
 Product Material

**Physical**

Tin - Electro Plated  
 Yellow  
 Y  
 16  
 Copper

UL Listed  
 CSA Certified  
 ROHS Compatible  
 UL Recognized  
 CULUS  
 Industry Standards

**Approvals / Certifications**

Y  
 Y  
 Compliant  
 N  
 N  
 UL467

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47, industrial Park Drive  
 Manchester NH03109

**BURNDY Technical Servcies**

47, industrial Park Drive  
 Manchester NH03109

Hours: 8.00 AM - 5.00 PM  
 Monday - Friday  
 Phone: 000-346-4175