



## On Line Catalog



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YA2C2TC38  
 7818105035155  
 HYLUG-2STR-(2)3/8STUD  
 Active

**Web Use**  
 BURNDY Product Line

### Dimensional

Tongue Angle  
 Length (in)  
 Tongue Type  
 Barrell Style  
 Bolt Hole Size (in)  
 Barrel Type  
 Thickness  
 B Length (in)  
 Pad Width (in)  
 E - in  
 Strip Length

Straight  
 3.42  
 Standard  
 Chamfered  
 0.39  
 Long  
 0.11  
 1.25  
 0.60  
 1.00  
 1-5/16

### General

Number of Holes  
 Product Description

2  
 Copper Compression Lug, 2 Hole  
 w/o Inspection Window, 2 AWG,  
 3/8" Stud, 1" Stud Hole Spacing,  
 Long Barrel, Tin Plated

### Conductor(s)

Flex (Class G) Size - Range  
 Flex (Class H) Size - Range  
 Flex (Class I) Size - Range  
 Copper Solid Size (Range)  
 DLO Size (Range)  
 Copper Stranded (Range)

N/A  
 N/A  
 N/A  
 2 AWG  
 N/A  
 2 AWG

### Physical


Type of Plating  
 Bolt Hole Size  
 Color Code  
 Plated (Yes or No)  
 Index Number  
 Product Material

Tin - Electro Plated  
 3/8  
 Brown  
 Y  
 10  
 Copper

### Approvals / Certifications

UL Listed  
 CSA Certified  
 ROHS Compatible  
 UL Recognized  
 CULUS  
 Industry Standards  
**Documentation**

Y  
 Y  
 Compliant  
 N  
 N  
 UL468A-468B



For further technical assistance, please contact us