



BURNDY Catalog Number
UPC Number
Description
Status

YA2CL4
 7818100995200
 COPPER HYLUG BULK PACKAG
 Active

Web Use
 BURNDY Product Line

Tongue Angle
 Length (in)
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 Strip Length

Dimensional

Straight
 2.06
 Chamfered,Skived
 0.39
 Standard
 0.11
 0.88
 0.61
 15/16

Number of Holes

General

1
 Cu Comp Terminal Code Cond, Bvl
 Entry, 1 Hole/W/InspWindow, #2
 AWG Str Code,60 Navy, 600 V-35
 kV, 3/8" Stud, Std bbl, Tin Plated,
 Brown, 10 Index

Product Description

Conductor(s)

Flex (Class G) Size - Range
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Copper Solid Size (Range)
 DLO Size (Range)
 Copper Stranded (Range)

N/A
 N/A
 N/A
 N/A
 N/A
 2 AWG

Physical

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Tin - Electro Plated
 3/8
 Brown
 Y
 10
 Copper

Approvals / Certifications

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS
 Industry Standards

Y
 Y
 Compliant
 N
 N
 UL467

Documentation

For further technical assistance, please contact us