



BURNDY Catalog Number
UPC Number
Description
Status

YA312TC38
 7818108213055
 CU HYLUG-350 KCMIL-3/8X1
 Active

Web Use
 BURNDY Product Line

Tongue Angle
 Length (in)
 Tongue Type
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 E - in
 Strip Length

Dimensional

Straight
 4.49
 Standard
 Chamfered
 0.39
 Long
 0.18
 2.00
 1.29
 1.00
 2-1/16

Number of Holes

General

2
 Cu Comp Terminal Code Cond, Bvl
 Entry, 2 Hole/W/O/InspWindow,
 350 kcmil, 350 Navy, 600 V-35
 kV, 3/8" Stud, 1.00" Spacing, Lng
 bbl, Red, 18 or 324 Index

Product Description

Conductor(s)

Flex (Class G) Size - Range
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Copper Solid Size (Range)
 DLO Size (Range)
 Copper Stranded (Range)

N/A
 N/A
 N/A
 N/A
 N/A
 350 kcmil

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Physical

Tin - Electro Plated
 3/8
 Red
 Y
 18,324
 Copper

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS
 Industry Standards

Approvals / Certifications

Y
 Y
 Compliant
 N
 N
 UL468A-468B

Documentation

For further technical assistance, please contact us