



BURNDY Catalog Number YA342TC38
UPC Number 7818108212377
Description CULUG-500KCM-3/8X1
Status Active

Web Use
 BURNDY Product Line

Dimensional	
Tongue Angle	Straight
Length (in)	4.90
Tongue Type	Standard
Barrell Style	Chamfered
Bolt Hole Size (in)	0.39
Barrel Type	Long
Thickness	0.23
B Length (in)	2.25
Pad Width (in)	1.55
E - in	1.00
Strip Length	2-5/16
General	
Number of Holes	2
Product Description	Copper Compression Lug, 2 Hole w/o Inspection Window, 500 kcmil, 3/8" Stud, 1" Stud Hole Spacing, Long Barrel, Tin Plated
Conductor(s)	
Flex (Class G) Size - Range	N/A
Flex (Class H) Size - Range	N/A
Flex (Class I) Size - Range	N/A
Copper Solid Size (Range)	N/A
DLO Size (Range)	N/A
Copper Stranded (Range)	500 kcmil
Physical	
Type of Plating	Tin - Electro Plated
Bolt Hole Size	3/8
Color Code	Brown
Plated (Yes or No)	Y
Index Number	20,299
Product Material	Copper
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA
 47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services
 47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175