



On Line Catalog



BURNDY Catalog Number YA34LTC12FX
UPC Number 7818105432144
Description CU 350FLEX STDBARREL 1/2STUD
Status TC
Active

Web Use
BURNDY Product Line

Dimensional
Tongue Angle Straight
Length (in) 3.12
Tongue Type Standard
Barrell Style Chamfered
Bolt Hole Size (in) 0.52
Barrel Type Standard
Thickness 0.23
B Length (in) 1.27
Pad Width (in) 1.55
Strip Length 1-5/16

General
Number of Holes 1
Product Description Copper Compression Lug, 1 Hole
w/ Inspection Window, 350 Flex,
1/2" Stud, Short Barrel, Tin Plated

Conductor(s)
Flex (Class G) Size - Range 350 kcmil
Flex (Class H) Size - Range 350 kcmil
Flex (Class I) Size - Range 350 kcmil
Copper Solid Size (Range) N/A
DLO Size (Range) 373.7 (925/#24) DLO
Copper Stranded (Range) N/A

Physical
Type of Plating Tin
Bolt Hole Size 1/2
Color Code Blue
Plated (Yes or No) Y
Index Number 19,470
Product Material Copper

Approvals / Certifications
UL Listed Y
CSA Certified Y
ROHS Compatible Compliant
UL Recognized N
CULUS N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

BURNDY Technical Services

Hours: 8:00 AM - 5:00 PM
Monday - Friday
Phone: 800-346-4175