



On Line Catalog



BURNDY Catalog Number	YA34LTC38FX
UPC Number	7818101346588
Description	CULUG 350 FLEX 3/8 STUD
Status	Active

Web Use
BURNDY Product Line

Dimensional	
Tongue Angle	Straight
Length (in)	2.87
Barrell Style	Chamfered
Bolt Hole Size (in)	0.39
Barrel Type	Standard
Thickness	0.23
B Length (in)	1.27
Pad Width (in)	1.55
Strip Length	1-5/16
General	
Number of Holes	1
Product Description	Copper Compression Lug, 1 Hole w/ Inspection Window, 350 Flex, 3/8" Stud, Short Barrel, Tin Plated
Conductor(s)	
Flex (Class G) Size - Range	350 kcmil
Flex (Class H) Size - Range	350 kcmil
Flex (Class I) Size - Range	350 kcmil
Copper Solid Size (Range)	N/A
DLO Size (Range)	373.7 (925/#24) DLO
Copper Stranded (Range)	N/A
Physical	
Type of Plating	Tin
Bolt Hole Size	3/8
Color Code	Blue
Plated (Yes or No)	Y
Index Number	19,470
Product Material	Copper
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA
47, industrial Park Drive
Manchester NH03109

BURNDY Technical Servcies
47, industrial Park Drive
Manchester NH03109

Hours: 8.00 AM - 5.00 PM
Monday - Friday
Phone: 000-346-4175