




On Line Catalog



BURNDY Catalog Number
UPC Number
Description
Status

YA36L
 7818105216011
 CUHYLUG-600 KCMIL-5/8
 Active

Web Use
 BURNDY Product Line

Tongue Angle
 Length (in)
 Tongue Type
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 Strip Length

Dimensional

Straight
 3.54
 Standard
 Chamfered,Skived
 0.66
 Standard
 0.27
 1.38
 1.74
 1-3/4

Number of Holes

General

1
 Cu Comp Terminal Code Cond, Bvl
 Entry, 1 Hole/W/InspWindow, 600
 kcmil Str Code, 600 V-35 kV, 5/8"
 Stud, Std bbl, Tin Plated, Green,
 22 or 472 Index

Product Description

Conductor(s)

Flex (Class G) Size - Range
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Copper Solid Size (Range)
 DLO Size (Range)
 Copper Stranded (Range)

N/A
 N/A
 N/A
 N/A
 N/A
 600 kcmil

Physical

Type of Plating
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Tin - Electro Plated
 Green
 Y
 22,472
 Copper

Approvals / Certifications

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS
 Industry Standards

Y
 Y
 Compliant
 N
 N
 UL467

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

BURNDY Technical Services

Hours: 8:00 AM - 5:00 PM
 Monday - Friday