



[On Line Catalog](#)
**BURNDY Catalog Number**

YA392N

**UPC Number**

7818105223566

**Description**

750 CU 2-HOLE LONG NEMA

**Status**

Active

**Web Use**

BURNDY Product Line

**Dimensional**

|                     |           |
|---------------------|-----------|
| Tongue Angle        | Straight  |
| Length (in)         | 6.87      |
| Tongue Type         | Standard  |
| Barrell Style       | Chamfered |
| Bolt Hole Size (in) | 0.52      |
| Barrel Type         | Long      |
| Thickness           | 0.27      |
| B Length (in)       | 2.88      |
| Pad Width (in)      | 1.91      |
| E - in              | 1.75      |
| Strip Length        | 2-15/16   |

**General**

|                     |   |
|---------------------|---|
| Number of Holes     | 2   |
| Product Description | Copper Compression Lug, 2 Hole w/o Inspection Window, 750 kcmil, 1/2" Stud, 1-3/4" Stud Hole Spacing, Long Barrel, Tin Plated |

**Conductor(s)**

|                             |           |
|-----------------------------|-----------|
| Flex (Class G) Size - Range | N/A       |
| Flex (Class H) Size - Range | N/A       |
| Flex (Class I) Size - Range | N/A       |
| Copper Solid Size (Range)   | N/A       |
| DLO Size (Range)            | N/A       |
| Copper Stranded (Range)     | 750 kcmil |

**Physical**

|                    |        |
|--------------------|--------|
| Type of Plating    | Tin    |
| Bolt Hole Size     | 1/2    |
| Color Code         | Black  |
| Plated (Yes or No) | Y      |
| Index Number       | 24     |
| Product Material   | Copper |

**Approvals / Certifications**

|                    |             |
|--------------------|-------------|
| UL Listed          | Y           |
| CSA Certified      | Y           |
| ROHS Compatible    | Compliant   |
| UL Recognized      | N           |
| CULUS              | N           |
| Industry Standards | UL468A-468B |

**Documentation**

For further technical assistance, please contact us