



[On Line Catalog](#)


BURNDY Catalog Number YA462N
UPC Number 7818105247566
Description 1500 CU 2-HOLE LONG 1/2
Status Active

Web Use
 BURNDY Product Line

Dimensional

| | |
|---------------------|-----------|
| Tongue Angle | Straight |
| Length (in) | 7.55 |
| Tongue Type | Standard |
| Barrell Style | Chamfered |
| Bolt Hole Size (in) | 0.52 |
| Barrel Type | Long |
| Thickness | 0.40 |
| B Length (in) | 3.19 |
| Pad Width (in) | 2.69 |
| E - in | 1.75 |
| Strip Length | 3-1/4 |

General

| | |
|---------------------|--|
| Number of Holes | 2 |
| Product Description | Copper Compression Lug, 2 Hole w/o Inspection Window, 1500 kcmil, 1/2" Stud, 1-3/4" Stud Hole Spacing, Long Barrel, Tin Plated |

Conductor(s)

| | |
|-----------------------------|------------|
| Flex (Class G) Size - Range | N/A |
| Flex (Class H) Size - Range | N/A |
| Flex (Class I) Size - Range | N/A |
| Copper Solid Size (Range) | N/A |
| DLO Size (Range) | N/A |
| Copper Stranded (Range) | 1500 kcmil |

Physical

| | |
|--------------------|----------------------|
| Type of Plating | Tin - Electro Plated |
| Bolt Hole Size | 1/2 |
| Color Code | Green |
| Plated (Yes or No) | Y |
| Index Number | 31 |
| Product Material | Copper |

Approvals / Certifications

| | |
|--------------------|-------------|
| UL Listed | Y |
| CSA Certified | Y |
| ROHS Compatible | Compliant |
| UL Recognized | N |
| CULUS | N |
| Industry Standards | UL468A-468B |

Documentation

For further technical assistance, please contact us