



BURNDY Catalog Number
UPC Number
Description
Status

YA4CL3BOX
 7818105524388
 CULUG- 4 STR-SHORT-5/16
 Active

Web Use
 BURNDY Product Line

Tongue Angle
 Length (in)
 Tongue Type
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 Strip Length

Dimensional

Straight
 1.79
 Standard
 Chamfered,Skived
 0.33
 Standard
 0.08
 0.81
 0.50
 7/8

Number of Holes

General

1
 CU Compression Terminal Code
 Conductor, Beveled Entry, 1
 Hole/W/InspWindow,
 #4AWG(Code) 40(Navy), 600V-
 35kV, 5/16" Stud, Standard
 Barrel, Electro-Tin Plated

Product Description

Conductor(s)

Flex (Class G) Size - Range
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Copper Solid Size (Range)
 DLO Size (Range)
 Copper Stranded (Range)

N/A
 N/A
 N/A
 N/A
 N/A
 4 AWG

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Physical

Tin - Electro Plated
 5/16
 Gray
 Y
 8
 Copper

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS

Approvals / Certifications

Y
 Y
 Compliant
 N
 N

Documentation

For further technical assistance, please contact us