



BURNDY Catalog Number
UPC Number
Description
Status

YA8CL2TC10
 7818105035844
 CU HYLUG-8 STR-(2) 10 ST
 Active

Web Use
 BURNDY Product Line

Tongue Angle
 Length (in)
 Tongue Type
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 E - in
 Strip Length

Dimensional

Straight
 1.83
 Standard
 Chamfered
 Standard
 0.08
 0.44
 0.41
 0.62
 7/16

Number of Holes

General

2
 Copper Compression Lug, 2 Hole
 w/ Inspection Window, 8 AWG/6
 AWG, #10 Stud, 5/8" Stud Hole
 Spacing, Short Barrel, Tin - Electro
 Plated

Product Description

Conductor(s)

Flex (Class G) Size - Range
 Flex (Class H) Size - Range
 Flex (Class I) Size - Range
 Copper Solid Size (Range)
 DLO Size (Range)
 Copper Stranded (Range)

N/A
 N/A
 N/A
 N/A
 N/A
 8 AWG

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Physical

Tin - Electro Plated
 #10
 Red
 Y
 49
 Copper

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS
 Industry Standards

Approvals / Certifications

Y
 Y
 Compliant
 N
 N
 UL468A-468B

Documentation

For further technical assistance, please contact us