



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YAV28TC38FXB  
 7818100808322  
 BELLED HYLUG-4/0 FLEX-3/  
 Active

**Web Use**  
 BURNDY Product Line

Tongue Angle  
 Length (in)  
 Tongue Type  
 Barrell Style  
 Bolt Hole Size (in)  
 Barrel Type  
 Thickness  
 B Length (in)  
 Pad Width (in)  
 Strip Length

**Dimensional**  
 Straight  
 3.19  
 Standard  
 Belled  
 0.39  
 Long  
 0.14  
 1.77  
 1.14  
 1-7/8

Number of Holes

**General**

1  
 Copper Compression Lug, 1 Hole  
 w/o Inspection Window, 4/0 AWG  
 / 250 FLEX, 3/8" Stud, Long  
 Barrel, Belled End, Tin Plated

Product Description

**Conductor(s)**

Aircraft Cable Size (Range)  
 Flex (Class H) Size - Range  
 Flex (Class I) Size - Range  
 Copper Solid Size (Range)  
 DLO Size (Range)  
 Navy Cable Size (Range)  
 Copper Stranded (Range)  
 Flex (Class G) Size - Range  
 Flex (Class M) Size - Range

N/A  
 4/0 AWG  
 4/0 AWG  
 N/A  
 4/0 (550/#24) DLO  
 200 (61) Navy  
 4/0 AWG  
 1/0 AWG  
 4/0 AWG

Type of Plating  
 Bolt Hole Size  
 Color Code  
 Plated (Yes or No)  
 Index Number  
 Product Material

**Physical**

Tin - Electro Plated  
 3/8  
 Yellow  
 Y  
 16  
 Copper

UL Listed  
 CSA Certified  
 ROHS Compatible  
 UL Recognized  
 CULUS  
 Industry Standards

**Approvals / Certifications**

Y  
 Y  
 Compliant  
 N  
 N  
 UL468A-468B

**Documentation**

For further technical assistance, please contact us