



On Line Catalog



BURNDY Catalog Number
UPC Number
Description
Status

YAZ382NTCFX
 7818102286788
 CULUG-500FLX-LONG W/PORT
 Active

Web Use
 BURNDY Product Line

Tongue Angle
 Strip Length
 Length (in)
 Barrell Style
 Bolt Hole Size (in)
 Barrel Type
 Thickness
 B Length (in)
 Pad Width (in)
 E - in

Dimensional

Straight
 2-3/4
 6.72
 Skived
 0.52
 Long
 0.27
 2.81
 1.62
 1.75

Number of Holes

General

2
 Cu Comp Terminal Flex Cond, Bvl
 Entry, 2 Hole/W/InspWindow,
 535.3 kcmil(1325/#24)DLO, 500
 kcmil Flex, 600 V-35 kV, 1/2"
 Stud, 1.75" Spacing, Lng bbl

Product Description

Conductor(s)

Copper Solid Size (Range)
 Navy Cable Size (Range)
 Copper Stranded (Range)

N/A
 N/A
 N/A

Physical

Type of Plating
 Bolt Hole Size
 Color Code
 Plated (Yes or No)
 Index Number
 Product Material

Tin
 1/2
 Pink
 Y
 L99
 Copper

Approvals / Certifications

UL Listed
 CSA Certified
 ROHS Compatible
 UL Recognized
 CULUS

Y
 Y
 Compliant
 N
 N

Documentation

For further technical assistance, please contact us

BURNDY LLC - USA

47, industrial Park Drive
 Manchester NH03109

BURNDY Technical Servcies

47, industrial Park Drive
 Manchester NH03109

Hours: 8.00 AM - 5.00 PM
 Monday - Friday
 Phone: 000-346-4175

