



BURNDY Catalog Number YGLR29C34
UPC Number 7818102208255
Description 2-250 GRD GRID TO 3/4
 RO
Status Active

Web Use
 BURNDY Product Line

Dimensional	
Length (in)	2.63
B Length (in)	0.75
D - in	0.50
BB - Length (in)	0.88
B Length (Fraction)	3/4
General	
Product Description	Copper Compression Connector, Ground Rod to Grid, 2 AWG (Str) to 250 kcmil, 3/4" Ground Rod
Prefilled (Oxide Inhibitor)	Y
Other	
Type of Oxide Inhibitor	Penetrox E
Approvals / Certifications	
Rated for Direct Burial	Y
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL467,IEEE 837
Conductor(s)	
Rod Size (Side B) - Range	3/4 in
Copper Str Size (Side A) - Range	2 AWG-250 kcmil
Physical	
Type of Plating	Unplated
Die Index (Side B)	1011
Die Index (Side A)	997
Plated (Yes or No)	N
Product Material	Copper
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA
 47, industrial Park Drive
 Manchester NH03109

BURNDY Technical Servcies
 47, industrial Park Drive
 Manchester NH03109

Hours: 8.00 AM - 5.00 PM
 Monday - Friday
 Phone: 000-346-4175