



BURNDY Catalog Number
UPC Number
Description
Status

YAV102TC10
 7818100218355
 CULUG-14/10STR-2 10STUDS
 Active

Web Use
 BURNDY Product Line

Dimensional	
Tongue Angle	Straight
Length (in)	1.72
Tongue Type	Standard
Barrell Style	Chamfered
Bolt Hole Size (in)	0.20
Barrel Type	Standard
Thickness	0.06
B Length (in)	0.38
Pad Width (in)	0.36
E - in	0.62
Strip Length	7/16
General	
Number of Holes	2
Product Description	Copper Compression Lug, 2 Hole w/ Inspection Window, 14 AWG -10 AWG (str)/ 12 AWG-10 AWG (sol), #10 Stud, 5/8" Stud Hole Spacing, Short Barrel, Tin - Electro Plated
Conductor(s)	
Flex (Class G) Size - Range	N/A
Flex (Class H) Size - Range	N/A
Flex (Class I) Size - Range	N/A
Copper Solid Size (Range)	12 AWG-10 AWG
DLO Size (Range)	N/A
Copper Stranded (Range)	14 AWG-10 AWG
Physical	
Type of Plating	Tin - Electro Plated
Bolt Hole Size	#10
Plated (Yes or No)	Y
Product Material	Copper
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47 East Industrial Park Drive
 Manchester NH 03109

BURNDY Technical Services

47 East Industrial Park Drive
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM
 Monday - Friday
 Phone: 800-346-4175