



YCAB344N

by Burndy Catalog ID: YCAB344N

Prop65

Copper compression lug designed for terminating copper conductors to switch pads and other substation switch yard apparatus, Pad width: 2-3/8 IN.

Features: Compression HYLUG Terminals Designed For Terminating Copper Conductors To Switch Pads And Other Substation Or Switch Yard Apparatus, NEMA Standard Mounting Holes, Made Of Pure Copper, Installed With Same Die As Equivalent Full Tension Jumper Loop And Repair Sleeves, Have Brazed Pads, Tools, Die Set Catalog Number, And (number Of Crimps): Y35, Y750 Tool, U210 Die, (6), Y45 Tool, U210 Die With PT-6515 Adapter, (6), Y46 Tool, U210 Die With PUADP-1 Adapter, (6), Y48B Tool, C210 Die, (2), Y60BHU Tool, L210 Die, (2), Die Index: 210

Product Details

General

| Application | For Terminating Copper Conductors To Switch Pads And Other Substation Or Switch Yard Apparatus |
|--------------------------------------|---------------------------------------------------------------------------------------------------|
| Connector Type | Terminal |
| Die Index | 210 |
| Material | Copper |
| Physical Attribute - Number of Holes | 4 |
| Physical Attribute - Tongue Type | Standard |
| Plated | Ν |
| Plating Type | Tin |
| Prefilled Oxide Inhibitor | Ν |
| Sub Brand | HYLUG |
| Trade Name | HYLUG™ |
| Туре | YCAB-4N |
| UPC | 781810014851 |

Dimensions

| Dimension - B Length fraction | 2-9/17 in |
|-------------------------------------------|-----------|
| Dimension - B Length inch | 2.53 in |
| Dimension - D inch | 3.00 in |
| Dimension - F Width Center to Center inch | 1.75 in |
| Dimension - Hole Size fraction | 14/25 in |
| Dimension - Hole Size inch | 0.56 in |
| Dimension - Hole Size mm | 14 mm |
| Dimension - L Length Overall mm | 173 mm |
| Dimension - Length Overall inch | 6.81 in |
| Dimension - N inch | 0.62 in |
| Dimension - Outside Diameter inch | 1.38 in |

| Dimension - Pad Width inch | 3.00 in |
|-----------------------------------|----------|
| Dimension - Strip Length inch | 2 5/8 |
| Dimension - Stud Size inch | 1/2 |
| Dimension - Z inch | 0.63 in |
| Physical Attribute - Tongue Angle | Straight |

Conductor Related

| Conductor - Copper Str Size | 500 kcmil |
|-----------------------------------|-----------|
| Conductor - Copper Str Size Range | 500 kcmil |

Certifications and Compliance

| Certification - CSA Approved | No | |
|------------------------------------|----|--|
| Certification - ETL | No | |
| Certification - UL Recognized | No | |
| Certification - cULus | No | |
| Standards - RoHS Compliance Status | EX | |
| UL Listed | No | |
| Logistics | | |

Minimum Pack Quantity

1

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday Emergency Service 24-hours/365 Days Phone: 1-800-346-4175 1-603-647-5299 (International)