

## SRG-K

SRG-K  
200°C - 600 Volt



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

---

- Annealed tinned copper

### Category Jacket Description:

---

- Aramid fiber braid

### Standards:

---

- NEMA WC 3 Flame Propagation Test
- IEEE 1202 Vertical Cable Tray Flame Test

### Category Insulation Description:

---

- Silicone rubber, fiberglass braid

### Applications:

---

- Used for leads to motors, transformers or other electrical equipment where hazardous and/or high temperature conditions exist requiring flexible heat resistant conductors at 600 volts

## Part Number Table

Part#	Gauge	Conductors	Stranding	Kevlar Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
C51403	14	3	7	.030"	0.4	75
C51404	14	4	7	.030"	0.435	100
C51405	14	5	7	.030"	0.48	125
C51407	14	7	7	.030"	0.52	170
C51203	12	3	19	.030"	0.43	110
C51204	12	4	19	.030"	0.475	145
C51205	12	5	19	.030"	0.52	175
C51207	12	7	19	.030"	0.57	240

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

**Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)**  
**Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •**  
**Seattle • St. Louis • Tampa • Toronto**  
**© 2020 Omni Cable LLC**