

DOUBLE CLEVIS (MID-LINK)

WORKING LOAD LIMIT: 4,700 TO 13,000 LBS.

Designed for use with Grade 70 chain as a quick and easy temporary repair.

BENEFITS & FEATURES

- Zinc-plated finish
- Size forged into link
- Quick easy installations
- Design factor 4:1



N THE USA

| For Chain Size (in.) | | Standard | Product | Dimensions (in.) | | | | | Weight | |
|----------------------------|--------|----------|---------|------------------|------|------|------|------|--------|--------|
| | | Package | Code | Α | В | C | D | E | F | (lbš.) |
| 1/4 and 5/16 | 4,700 | 10 | M605 | 0.43 | 0.38 | 1.70 | 1.12 | 2.61 | 0.91 | 0.35 |
| 3/8 | 6,600 | 10 | M606 | 0.50 | 0.38 | 2.00 | 1.31 | 3.06 | 1.09 | 0.46 |
| 7/16 and 1/2 | 11,300 | 5 | M608 | 0.66 | 0.59 | 2.59 | 1.74 | 3.90 | 1.31 | 1.10 |
| 5/8 | 13,000 | 5 | M610 | 0.75 | 0.75 | 2.81 | 2.01 | 4.31 | 1.50 | 1.70 |

NOTE: 1/4" through 1/2" sizes are individually bagged

142