

General Purpose Clevis—Big Orange®



Hot forged carbon steel. Supplied with alloy pin for extra strength. Painted orange.

Part Number	UPC 043927-	Body Size	Standard Pack	Approx. Wt. Ea. (lbs.)
M465	42831-1	3/4	5	3.0

Working Load Limit (WLL) 10,000 lbs.

Twist Clevis—Big Orange®

Hot forged carbon steel. Painted orange. Alloy Tee handle clevis pin.



Part Number	UPC 043927-	Body Size	Std. Pack	WLL (Lbs.)	Approx. Wt. Ea. (lbs.)
M8258	42750-5	5/8	5	6,000	1.5
M8234	42757-4	3/4	5	12,000	2.3
M8078	42789-5	7/8	5	16,000	3.0
M8278	42764-2	7/8	5	16,000	3.6
M8290	42774-1	15/16	5	20,000	4.2
M8295	42782-6	1	5	25,000	6.0

Straight Clevis—Big Orange®

Hot forged carbon steel. Alloy Tee handle clevis pin.



Part Number	UPC 043927-	Body Size	Std. Pack	WLL (Lbs.)	Approx. Wt. Ea. (lbs.)
M8158	42701-7	5/8	5	6,000	1.5
M8134	42705-5	3/4	5	12,000	2.3
M8878	42742-0	7/8	5	16,000	3.0
M8178	42712-3	7/8	5	16,000	3.6
M8190	42723-9	15/16	5	20,000	4.2
M8195	42734-5	1	5	25,000	6.0

Utility Clevis—Big Orange®

Hot forged micro alloy steel, heat treated. Supplied with micro alloy pin. Painted orange.



Part Number	UPC 043927-	Body Size	Std. Pack	WLL (Lbs.)	Approx. Wt. Ea. (lbs.)
M1546	40816-0	1/4	25	1,000	.08
M1547	40817-7	5/16	25	1,500	.20
M1548	40818-4	3/8	25	2,000	.28
M1549	42823-6	7/16	25	3,000	.40
M1550	42828-1	1/2	25	4,000	.62
M1551	42829-8	5/8	25	6,500	1.2

M1548 and M1549 are used for joining hitch to harrow sections.

Farm Screw Pin Clevis—Big Orange®

Hot forged micro alloy steel, heat treated. Alloy pin.



Part Number	UPC 043927-	Body Size	Std. Pack	WLL (Lbs.)	Approx. Wt. Ea. (lbs.)
M1646	42796-3	1/4	25	1,000	.12
M1647	42797-0	5/16	25	1,500	.20
M1648	42798-7	3/8	25	2,000	.32
M1649	42799-4	7/16	10	3,000	.50
M1650	42804-5	1/2	10	4,000	.75
M1651	42805-2	5/8	10	6,500	1.2
M1652	42806-9	3/4	5	9,500	2.2
M1653	42807-6	7/8	5	13,000	3.5
M1654	42808-3	1	5	17,000	5.2
M1655	42809-0	1 1/8	Bulk	24,000	7.0
M1656	42810-6	1 1/4	Bulk	28,000	9.5

For use on multiple hitches where 3 or 4 implements are pulled with one tractor.

! WARNING ! Improper use or care of shackles/clevises can result in bodily injury or property damage.

To Avoid Injury: • Do not exceed working load limit. • Do not shock or impact load. • Do not side load—center line of load must coincide with the center line of shackle/clevis. • Do not replace pin or bolt with other than original equipment parts. • Inspect before use for wear, deformation, and pin engagement.

Replacement Tee Handle Clevis Pins—Big Orange®

Hot forged micro alloy steel, heat treated.



Part Number	UPC# 043927-	For Clevis Number	Diameter (In.)	Usable Length (In.)	Std. Pack	Approx. Wt. Ea. (Lbs.)
M811	43014-7	M8158 and M8258	1/2	2 1/4	20	.22
M813	43015-4	M8134 and M8234	5/8	3 3/8	20	.56
M817	43017-8	M8078, M8878, M8178 and M8278	3/4	3 3/4	10	.80
M819	43020-8	M8190 and M8290	7/8	3 3/4	10	1.2
M829	43023-9	M8195 and M8295	1	4 1/4	10	1.5

8000 Series Clevis Pin replacement (twist clevises and straight clevises pictured above). Pins are zinc plated with hair pin lock. Heat treated. Hot forged micro alloy steel, heat treated for optimum strength and durability.