
Applications:

Eaton's Crouse-Hinds non-metallic switch and outlet boxes are used:

- In branch circuit wiring as a splice point
- To mount wiring devices such as switches and receptacles
- To provide mechanical protection for wiring systems and electrical devices

Features:

- Available for use with wood or metal studs to meet any construction preference.
- Quick entry feature on all non-metallic boxes offers labor savings no need to break out knockouts – simply push the non-metallic cable into the box. No tools are required. No need to remove knockouts.
- Unique configuration of this quick entry feature on single gang boxes provides a self-feeding feature that eliminates the need to reach inside the box to pull the wire out.
- Integral labor saving clamping feature on two, three and four gang boxes. The multiple gang box unique entry also serves as a clamp, eliminating the need to mechanically secure the cable inside the box. There are no separate clamps or screws to install or tighten. Each entry into the multiple gang boxes has the quick entry feature allowing the installer to simply push the cable into the box without the need for tools or removal of knockouts, so the cable can be inserted where it is required.



Certifications and Compliances:

- UL Listed File No. E102328
- Classified for use in fire rated (2 HR) wall or ceiling. Fire Rating No. R9933.

Standard Materials:

• PVC-Polyvinyl Chloride Compound

SWITCH BOXES - ANGLED NAILS UL LISTED







TP1800 TP2000

TP2300

Cat. #	Bracket or Nails	Capacity Cu. In.	н	w	D	Unit Qty.	Wt. Lbs. Per 100	
TP1800	Nails	18.0	33/4"	21/4"	23/4"	100	23	
TP2000	Nails	20.3	33/4"	21/4"	33/16"	100	25	
TP2300	Nails	23.0	33/4"	21/4"	37/16"	100	27	

SWITCH BOXES - INTEGRAL CLAMPS UL LISTED





TP1690 (Old Work)

TP2030 (For Wood or Metal Studs)

Cat. #	Bracket or Nails	Capacity Cu. In.	н	w	D	Unit Qty.	Wt. Lbs. Per 100
TP1690	Swing Clips & Integral Clamps	16.0	35/8"	25/16"	23/4"	50	20
TP2030	Face Bracket (1/2" offset)	20.3	311/16"	21/4"	33/16"	100	24

LOW VOLTAGE PARTITION - TWO, THREE OR FOUR GANG PVC



TP1000, TP1001

Cat. #	Use with the following boxes	Unit Qty.	Wt. Lbs. Per 100	
TP1000	TP3600, TP4600	20	3	
TP1001	TP3490, TP3635, TP4635, TP6180	50	4	