



3/4" DRIVE

3/4" DRIVE 12 POINT SAE STANDARD LENGTH SOCKETS

- Surface Drive® technology reduces fastener rounding
- Chrome Vanadium alloy steel for long lasting durability
- Nickel chrome plated for long lasting protection



Cat. No.	System	Fastener Size	Length	Width	Height	Weight
CDS91	SAE	7/8"	4.92 in	1.42 in	2.36 in	0.47 lb
CDS92	SAE	15/16"	4.92 in	1.42 in	2.36 in	0.47 lb
CDS93	SAE	1"	4.96 in	1.50 in	2.36 in	0.57 lb
CDS94	SAE	1-1/16"	4.96 in	1.50 in	2.36 in	0.51 lb
CDS95	SAE	1-1/8"	4.96 in	1.58 in	2.36 in	0.60 lb
CDS97	SAE	1-1/4"	5.12 in	1.73 in	2.36 in	0.69 lb
CDS98	SAE	1-5/16"	5.16 in	1.81 in	2.36 in	0.74 lb
CDS99	SAE	1-3/8"	5.20 in	1.81 in	2.36 in	0.74 lb
CDS100	SAE	1-7/16"	5.20 in	1.97 in	2.36 in	0.95 lb
CDS101	SAE	1-1/2"	5.32 in	2.05 in	2.36 in	1.07 lb
CDS102	SAE	1-5/8"	5.39 in	2.20 in	2.36 in	1.25 lb
CDS103	SAE	1-11/16"	5.51 in	2.28 in	2.36 in	1.43 lb
CDS104	SAE	1-3/4"	5.51 in	2.36 in	2.36 in	1.43 lb
CDS105	SAE	1-13/16"	5.59 in	2.56 in	2.36 in	1.50 lb
CDS106	SAE	1-7/8"	5.71 in	2.56 in	2.36 in	1.58 lb
CDS107	SAE	2"	5.79 in	2.76 in	2.36 in	1.74 lb

SPARK PLUG SOCKETS

- Surface Drive® technology reduces fastener rounding
- Chrome Vanadium alloy steel for long lasting durability
- Nickel chrome plated for long lasting protection



Cat. No.	Drive Size	Fastener Size	Length	Width	Height	Weight
CSPS0	3/8"	5/8"	4.92 in	0.87 in	1.69 in	0.22 lb
CSPS1	3/8"	3/4"	4.88 in	1.02 in	1.69 in	0.32 lb
CSPS2	3/8"	13/16"	4.92 in	1.06 in	1.69 in	0.32 lb
CSPS3	1/2"	5/8"	4.96 in	0.87 in	1.69 in	0.23 lb
CSPS4	1/2"	13/16"	4.96 in	0.87 in	1.69 in	0.34 lb