

## CTM110C2



Article Number: 151-30404

Cable Tie Mount, 0.19" Hole Dia., 0.2" Max Tie Width, PA66, White, 100/pkg



### Base Data

|                       |  |
|-----------------------|--|
| Local Order Number    | CTM110C2   |
| Type                  | CTM1   |
| Color                 | White (WH)   |
| Features and Benefits | <ul style="list-style-type: none"><li>• Designed for use with 18 through 50 pound cable ties to provide stability when securing bundles.</li><li>• Secures with a single screw providing quick installation.</li></ul> |
| Product Description   | HellermannTyton cable tie mounts are designed for use with 18 through 120 pound cable ties to provide stability when securing bundles. The mounts are installed quick and easy by securing a single screw.             |
| Fixation Method (FF)  | Screw Mounting and Rivet   |
| Short Description     | Cable Tie Mount, 0.19" Hole Dia., 0.2" Max Tie Width, PA66, White, 100/pkg   |

### Product Dimensions

|                                     |         |
|-------------------------------------|---------|
| Length L (imperial)                 | 0.58 "  |
| Length L (metric)                   | 14.7 mm |
| Width W (imperial)                  | 0.37 "  |
| Width W (metric)                    | 9.4 mm  |
| Cable Tie Width Max (imperial)      | 0.2 "   |
| Cable Tie Width max. (metric)       | 5.0 mm  |
| Height H (imperial)                 | 0.27 "  |
| Height H (metric)                   | 6.9 mm  |
| Mounting Hole Diameter D (imperial) | 0.19 "  |
| Mounting Hole Diameter D (metric)   | 4.8 mm  |

### Logistics and Packaging

|                  |       |
|------------------|-------|
| Quantity per     | bag   |
| Package Quantity | 100   |
| Carton Quantity  | 10000 |

### Material and Specifications

|                               |                                      |
|-------------------------------|--------------------------------------|
| Material                      | Polyamide 6.6 (PA66)                 |
| Material Shortcut             | PA66                                 |
| CSA Certified                 | No                                   |
| Flammability                  | UL94 V2                              |
| Operating Temperature         | -40 °F to +185 °F (-40 °C to +85 °C) |
| ROHS Conformity               | Yes                                  |
| Certification / Specification | UL                                   |

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes