

## Affordable Quality

# **COMMERCIAL AIR CIRCULATORS - 115V OSCILLATING MODELS**

### FEATURES

- Packaged in One UPS Shippable Carton
  Adjustable Pedestal (5' 8')
  32" Diameter Base

- Wall/Ceiling Mounts with Safety Cable Included
- All Stocked

#### **PERFORMANCE 115V**

Prop	CFM			RPM			FI
Dia.	High	Med	Low	High	Med	Low	Amps
24"	4400	3460	2460	1100	800	600	3.2
30"	6100	4400	2700	1100	800	600	3.2

#### **OSCILLATING MODELS - UNIT PACKS - 1/3 HP**

Prop Dia.		EDP Number		HP	Ship Wt.	List Price
24"	Adjustable Floor (S.B.)	71580	CA240AP (3-SP)	1/3	78	\$501
27	Wall Mount	71583	CA24OW (3-SP)	1/3	46	\$370
30"	Adjustable Floor (S.B.)	71581	CA300AP (3-SP)	1/3	95	\$524
	Wall Mount	71582	CA30OW (3-SP)	1/3	57	\$394

Unit Pack = Motor, Specified Style Mounting, Propeller, Base & Guard shipped in a single carton



- 115V, 1/3 HP, Oscillating,1 Phase, 3 Speed, Totally Enclosed Air Over Ball Bearing Motor
   Galvanized Steel Propeller
- 2 Year Warranty
- 15' Cord and Three Prong Plug Included
- UL and CUL Listed




Oscillating Adustable Pedestal



Oscillating Wall Mount

A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12 feet of 1/16" diameter cable, 2 cable clamps and instructions.

- 12 -



	TILT(IN DEGREES)				
	OSCILLATING				
TYPE	UP	DOWN			
FLOOR	20°	20°			
WALL	0°	20°			
0° = Horizontal Plane					

0° = Horizontal Plane