



## SCREWDRIVERS



**18V XRP™ 1/4" (13 mm) Drywall/Deck Screwdriver Kit**



**12V MAX\* Lithium Ion 1/4" (13 mm) Screwdriver Kit**



**7.2V 1/4" (6.35 mm) Two-Position Screwdriver Kit**

| SPECIFICATIONS      | DC520KA   | DCF610S2                                | DW920K-2                  |
|---------------------|---|---|---------------------------|
| Volts               | 18V   | 12V MAX*                                | 7.2V                      |
| Drive Size          | 1/4"  | 1/4"                                    | 1/4" Hex                  |
| No Load Speed       | 0 - 900 / 0 - 2,900 rpm   | 0 - 1,050 rpm                           | 0 - 500 rpm               |
| Chuck               | -   | 1-Handed Loading, 1/4" Hex Chuck        | 1/4" Hex chuck            |
| Max Torque (in-lbs) | 180 in-lbs  | -                                       | 80 in-lbs                 |
| Max Power           | -   | 160 UW0                                 | -                         |
| Capacity (CRS)      | 12 gauge  | -                                       | -                         |
| LEDs                | -   | 3                                       | -                         |
| Length              | -   | 6-1/4"                                  | -                         |
| Weight              | 5.1 lbs   | 2.2 lbs                                 | 3.5 lbs                   |
| Charger/Batteries   | 1-Hour Charger / (2) 18V XRP™                                   | Fast Charger / (2) 12V MAX* Lithium Ion | 1-Hour Charger / (2) 7.2V |
| Includes            | Bit tip / magnetic holder, drywall nosepiece, & TEKS® nosepiece | (1) Belt hook                           | -                         |

## SCREWDRIVERS



**8V MAX\* Gyroscopic Inline Screwdriver With Accessory Kit**



**8V MAX\* Gyroscopic Screwdriver With Conduit Reamer Kit**



**8V MAX\* Gyroscopic Screwdriver Kit**

| SPECIFICATIONS    | DCF682N1                                     | DCF681N2                                       | DCF680N2                                       |
|-------------------|--|--|--|
| Volts             | 8V MAX*                                      | 8V MAX*  | 8V MAX*  |
| Drive Size        | 1/4" Hex                                     | 1/4" Hex                                       | 1/4" Hex                                       |
| No Load Speed     | 0 - 430 rpm                                  | 0 - 430 rpm                                    | 0 - 430 rpm                                    |
| Chuck             | 1-Handed Loading, 1/4" Hex Chuck             | 1-Handed Loading, 1/4" Hex Chuck               | 1-Handed Loading, 1/4" Hex Chuck               |
| Motion Activated  | Yes  | Yes  | Yes  |
| LEDs              | 1  | 3  | 3  |
| Weight            | 1.1 lbs                                      | 1.25 lbs                                       | 1.1 lbs  |
| Charger/Batteries | 1-Hour Charger / (1) 8V MAX* Compact Battery | 1-Hour Charger / (2) 8V MAX* Compact Batteries | 1-Hour Charger / (2) 8V MAX* Compact Batteries |
| Includes          | (31) Piece Screwdriving Set                  | -  | -  |

With respect to 8V MAX\* - \*Maximum initial battery voltage (measured without a workload) is 8 volts. Nominal voltage is 7.2. TEKS® is a registered trademark of Illinois Tool Works, Inc.