

IMPACT WRENCHES



20V MAX* 1/2" (13 mm) Impact Wrench Kit with Hog Ring Anvil



20V MAX* 1/2" (13 mm) Impact Wrench Kit with Detent Pin



20V MAX* 1/2" (13 mm) Impact Wrench with Detent Pin (Tool Only)



20V MAX* 1/2" (13 mm) Impact Wrench Kit with Hog Ring Anvil

SPECIFICATIONS

	DCF889HM2	DCF880M2	DCF880B	DCF880HM2
Volts	20V MAX*	20V MAX*	20V MAX*	20V MAX*
Drive Size	1/2" Square w/ hog ring anvil	1/2" Square w/ detent pin anvil	1/2" Square w/ detent pin anvil	1/2" Square w/ hog ring anvil
Max Torque (in-lbs)	4,800 in-lbs	1,800 in-lbs	1,800 in-lbs	1,800 in-lbs
Max Torque (ft-lbs)	400 ft-lbs	150 ft-lbs	150 ft-lbs	150 ft-lbs
No Load Speed	0-1,500 rpm	0-2,300 rpm	0-2,300 rpm	0-2,300 rpm
Impacts/Minute	0-2,300 ipm	0-2,700 ipm	0-2,700 ipm	0-2,700 ipm
LEDs	1	3	3	3
Weight	6.7 lbs	3.4 lbs	2.2 lbs	3.4 lbs
Tool Length	10-3/4"	5-3/4"	5-3/4"	5-3/4"
Charger/Batteries	Charger / (2) 20V MAX* XR Lithium Ion (4.0 Ah)	Charger / (2) 20V MAX* XR Lithium Ion (4.0 Ah)	Sold Separately	Charger / (2) 20V MAX* XR Lithium Ion (4.0 Ah)



20V MAX* 3/8" (9.5 mm) Impact Wrench with Hog Ring Kit



20V MAX* 3/8" (9.5 mm) Impact Wrench with Hog Ring (Tool Only)



18V XRP™ 1/2" (13 mm) Impact Wrench Kit



18V 1/2" (13 mm) Impact Wrench (Tool Only)



18V XRP™ 3/8" (9.5 mm) Impact Wrench Kit

SPECIFICATIONS

	DCF883M2	DCF883B	DC820KA	DC820B	DC823KA
Volts	20V MAX*	20V MAX*	18V	18V	18V
Drive Size	3/8" Square w/ hog ring anvil	3/8" Square w/ hog ring anvil	1/2" Square w/ detent pin anvil	1/2" Square w/ detent pin anvil	3/8" Square w/ hog ring anvil
Max Torque (in-lbs)	1,560 in-lbs	1,560 in-lbs	1,740 in-lbs	1,740 in-lbs	1,500 in-lbs
Max Torque (ft-lbs)	130 ft-lbs	130 ft-lbs	145 ft-lbs	145 ft-lbs	125 ft-lbs
No Load Speed	0-2,300 rpm	0-2,300 rpm	0 - 2,400 rpm	0 - 2,400 rpm	0 - 2,400 rpm
Impacts/Minute	0-2,700 ipm	0-2,700 ipm	0 - 2,700 ipm	0 - 2,700 ipm	0 - 2,700 ipm
Weight	3.4 lbs	2.2 lbs	4.6 lbs	2.2 lbs	4.6 lbs
Tool Length	5-3/4"	5-3/4"	5-3/4"	5-3/4"	5-3/4"
Charger/Batteries	Charger / (2) 20V MAX* XR Lithium Ion (4.0 Ah)	Sold Separately	Charger / (2) 18V XRP™	Sold Separately	Charger / (2) 18V XRP™



18V 3/8" (9.5 mm) High Torque Impact Wrench (Tool Only)



18V XRP™ 1/2" (13 mm) High Torque Impact Wrench Kit with Detent Pin Anvil



18V 1/2" (13 mm) High Torque Impact Wrench with Detent Pin Anvil (Tool Only)



18V 1/2" (13 mm) High Torque Impact Wrench with Hog Ring Anvil (Tool Only)



12V MAX* 3/8" (9.5 mm) Impact Wrench Kit

SPECIFICATIONS

	DC823B	DW059K-2	DW059B	DW059HB	DCF813S2
Volts	18V	18V	18V	18V	12V MAX*
Drive Size	3/8" square w/ hog ring anvil	1/2" Square w/ detent pin anvil	1/2" Square w/ detent pin anvil	1/2" Square w/ hog ring anvil	3/8" Anvil
Max Torque (in-lbs)	1,500 in-lbs	3,600 in-lbs	3,600 in-lbs	3,600 in-lbs	1,150 in-lbs
Max Torque (ft-lbs)	125 ft-lbs	300 ft-lbs	300 ft-lbs	300 ft-lbs	96 ft-lbs
No Load Speed	0-2,400 rpm	1,650 rpm	1,650 rpm	1,650 rpm	0-2,450 rpm
Impacts/Minute	0-2,700 ipm	2,600 ipm	2,600 ipm	2,600 ipm	0-3,400 ipm
LEDs	1	-	-	-	3
Switch	Variable Speed	Rocker	Rocker	Rocker	Variable Speed
Weight	2.2 lbs	7.5 lbs	5.3 lbs	5.3 lbs	2.3 lbs
Tool Length	5-3/4"	10-3/4"	10-3/4"	10-3/4"	6-1/4"
Charger/Batteries	Sold Separately	Charger / (2) 18V XRP™	Sold Separately	Sold Separately	Charger / (2) 12V MAX* Lithium Ion