

ABS Case Liquid Filled Gauges

Feature:

- ASME B40.100, Grade B ($\pm 3-2-3\%$ accuracy)

PSI Range	Fig. Inter.	Minor Grad.	2½" Face ¼" Lower Mount Part #
0-15	3	.2	<i>GLP500</i>
0-30	5	.5	<i>GLP505</i>
0-60	10	1	<i>GLP510</i>
0-100	20	2	<i>GLP515</i>
0-160	20	2	<i>GLP517</i>
0-200	50	5	<i>GLP520</i>
0-300	50	5	<i>GLP525</i>
0-400	100	10	<i>GLP527</i>
0-600	100	10	<i>GLP530</i>
0-1000	200	20	<i>GLP535</i>
0-1500	300	20	<i>GLP540</i>
0-2000	500	50	<i>GLP545</i>
0-3000	500	50	<i>GLP550</i>
0-5000	1000	100	<i>GLP555</i>



Pneumatic
Accessories

Stainless Case Liquid Filled Gauges

Features:

- PowerFlex™ movement with polyester segment designed to resist the effects of shock, vibration and pulsation.
- ASME B40.100, Grade A ($\pm 2-1-2\%$ accuracy)
- copper alloy bourdon tube
- white aluminum dial with black numbers and black aluminum pointer
- ¼" NPT brass connection
- glycerin filled
- polycarbonate window
- temperature range: **-4°F to 150°F (-20°C to 65°C)**

PSI Range	Fig. Inter.	Minor Grad.	2½" Face ¼" Center Back Mount Part #	2½" Face, ¼" Lower Mount Part #
0-15	3	.5	<i>GLSC400</i>	<i>GLS400</i>
0-30	5	.5	<i>GLSC405</i>	<i>GLS405</i>
0-60	10	1	<i>GLSC410</i>	<i>GLS410</i>
0-100	20	2	<i>GLSC415</i>	<i>GLS415</i>
0-160	20	2	<i>GLSC417</i>	<i>GLS417</i>
0-200	40	5	<i>GLSC420</i>	<i>GLS420</i>
0-300	50	5	<i>GLSC425</i>	<i>GLS425</i>
0-400	50	5	<i>GLSC427</i>	<i>GLS427</i>
0-600	100	10	<i>GLSC430</i>	<i>GLS430</i>
0-1000	200	10	<i>GLSC435</i>	<i>GLS435</i>
0-1500	300	50	<i>GLSC440</i>	<i>GLS440</i>
0-2000	400	20	<i>GLSC445</i>	<i>GLS445</i>
0-3000	500	50	<i>GLSC450</i>	<i>GLS450</i>
0-5000	1000	100	<i>GLSC455</i>	<i>GLS455</i>



GLSC420



GLS430