

Dixon® Worm Gear Clamps

Features:

- clamp meets SAEJ1508 which supercedes Mil Spec WW-C-440B
- four-piece construction
- screw design: 5/16" slotted hex head
- maximum recommended torque 50 in. lbs.
- **all clamps sold 10 per box**

Style HS material:

- band and housing: SAE 300 series stainless
- screw: SAE 1018 case-hardened, hex-free chrome zinc-plated steel

Style HSS material:

- band and housing: SAE 300 series stainless
- screw: SAE 300 series stainless

| Band Width | Hose OD  |              | style HS Part # | Master Case Qty | style HSS Part # | Master Case Qty |
|------------|----------|--------------|-----------------|-----------------|------------------|-----------------|
|            | from     | to           |                 |                 |                  |                 |
| 1/2"       | 7/16"    | 25/32"       | <b>HS6</b>      | 200             | <b>HSS6</b>      | 200             |
|            | 1/2"     | 29/32"       | <b>HS8</b>      | 200             | <b>HSS8</b>      | 200             |
|            | 9/16"    | 1-1/16"      | <b>HS10</b>     | 500             | <b>HSS10</b>     | 500             |
|            | 11/16"   | 1-1/14"      | <b>HS12</b>     | 500             | <b>HSS12</b>     | 500             |
|            | 13/16"   | 1-1/2"       | <b>HS16</b>     | 500             | <b>HSS16</b>     | 500             |
|            | 13/16"   | 1-3/4"       | <b>HS20</b>     | 500             | <b>HSS20</b>     | 500             |
|            | 1-1/16"  | 2"           | <b>HS24</b>     | 500             | <b>HSS24</b>     | 500             |
|            | 1-5/16"  | 2-1/4"       | <b>HS28</b>     | 500             | <b>HSS28</b>     | 500             |
|            | 1-9/16"  | 2-1/2"       | <b>HS32</b>     | 500             | <b>HSS32</b>     | 500             |
|            | 1-13/16" | 2-3/4"       | <b>HS36</b>     | 500             | <b>HSS36</b>     | 500             |
|            | 2-1/16"  | 3"           | <b>HS40</b>     | 200             | <b>HSS40</b>     | 200             |
|            | 2-5/16"  | 3-1/4"       | <b>HS44</b>     | 200             | <b>HSS44</b>     | 200             |
|            | 2-9/16"  | 3-1/2"       | <b>HS48</b>     | 200             | <b>HSS48</b>     | 200             |
|            | 2-13/16" | 3-3/4"       | <b>HS52</b>     | 200             | <b>HSS52</b>     | 200             |
|            | 3-1/16"  | 4"           | <b>HS56</b>     | 200             | <b>HSS56</b>     | 200             |
|            | 3-5/16"  | 4-1/4"       | <b>HS60</b>     | 200             | <b>HSS60</b>     | 200             |
| 9/16"      | 3-9/16"  | 4-1/2"       | <b>HS64</b>     | 200             | <b>HSS64</b>     | 200             |
|            | 1-7/8"   | 5"           | <b>HS72</b>     | 100             | <b>HSS72</b>     | 100             |
|            | 2-1/2"   | 5-1/2"       | <b>HS80</b>     | 100             | <b>HSS80</b>     | 100             |
|            | 3-1/8"   | 6"           | <b>HS88</b>     | 100             | <b>HSS88</b>     | 100             |
|            | 3-5/8"   | 6-1/2"       | <b>HS96</b>     | 100             | <b>HSS96</b>     | 100             |
|            | 4-1/8"   | 7"           | <b>HS104</b>    | 100             | <b>HSS104</b>    | 100             |
|            | 5-5/8"   | 8-1/2"       | <b>HS128</b>    | 100             | <b>HSS128</b>    | 100             |
|            | 7-1/8"   | 10"          | <b>HS152</b>    | 100             | <b>HSS152</b>    | 100             |
|            | 9-3/8"   | 12-1/4"      | <b>HS188</b>    | 100             | <b>HSS188</b>    | 100             |
|            | 10-1/8"  | 13"          | <b>HS200</b>    | 100             | <b>HSS200</b>    | 100             |
|            | 10-7/8"  | 13-3/4"      | <b>HS212</b>    | 100             | <b>HSS212</b>    | 100             |
|            | 11-5/8"  | 14-1/2"      | <b>HS224</b>    | 100             | <b>HSS224</b>    | 100             |
|            | 12-3/8"  | 15-1/4"      | <b>HS236</b>    | 100             | <b>HSS236</b>    | 100             |
|            | 13-1/8"  | 16"          | <b>HS248</b>    | 100             | <b>HSS248</b>    | 100             |
| 17-1/8"    | 20"      | <b>HS312</b> | 100             | <b>HSS312</b>   | 100              |                 |



style HSS

Clamps



Miniature Worm Gear Clamps

Features:

- meets SAE J1508
- screw design: 1/4" slotted hex head
- maximum recommended torque 15 in. lbs.
- **all clamps sold 10 per box**

Style MH material:

- band and housing: SAE 300 series stainless
- screw: SAE 1018 case-hardened, hex-free chrome zinc-plated steel

Style MAH material:

- band and housing: SAE 300 series stainless
- screw: SAE 300 series stainless

| Band Width | Hose OD |         | style MH Part # | Master Case Qty | style MAH Part # | Master Case Qty |
|------------|---------|---------|-----------------|-----------------|------------------|-----------------|
|            | from    | to      |                 |                 |                  |                 |
| 5/16"      | 7/32"   | 5/8"    | <b>MH4</b>      | 500             | <b>MAH4</b>      | 500             |
|            | 7/16"   | 25/32"  | <b>MH6</b>      | 500             | <b>MAH6</b>      | 500             |
|            | 1/2"    | 29/32"  | <b>MH8</b>      | 200             | <b>MAH8</b>      | 200             |
|            | 9/16"   | 1-1/16" | <b>MH10</b>     | 200             | <b>MAH10</b>     | 200             |
|            | 11/16"  | 1-1/4"  | <b>MH12</b>     | 200             | <b>MAH12</b>     | 200             |
|            | 15/16"  | 1-1/2"  | <b>MH16</b>     | 200             | <b>MAH16</b>     | 200             |
|            | 1-3/16" | 1-3/4"  | <b>MH20</b>     | 200             | <b>MAH20</b>     | 200             |



style MH

Torque ratings correspond to the torque rating of the screw of the clamp and are not an indication of the working pressure of any hose assembly installed with this clamp. 