


## Double Bolt Clamps

### Features:

- inner surface has dual gripping ridges
- bolt lugs are reinforced to prevent bending out of alignment
- Torque values for clamps are based on dry bolts.
- The use of lubricant on bolts will adversely effect clamp performance. 
- measure hose OD accurately before ordering clamps
- Consult Dixon when using double bolt clamps on helical wire hose.



without saddles



with saddles

Hose OD		Plated Iron		Opt Qty	Torque in ft. lbs.
from	to	Part #	Price/E		
1-8/64"	1-12/64"	<b>J48</b>	<b>\$7.30</b>	100	15
1-12/64"	1-24/64"	<b>J49</b>	<b>9.00</b>	50	21
1-28/64"	1-34/64"	<b>JX49</b>	<b>12.10</b>	25	21
1-40/64"	1-52/64"	<b>DL14</b>	<b>13.20</b>	25	40
1-48/64"	2-3/64"	<b>DL20</b>	<b>13.25</b>	25	27
2-7/64"	2-19/64"	<b>DL24</b> <sup>1</sup>	<b>12.70</b>	25	27
2-20/64"	2-40/64"	<b>DL32</b> <sup>1</sup>	<b>13.70</b>	25	40
2-32/64"	2-48/64"	<b>DL275</b>	<b>17.40</b>	25	40
2-48/64"	3-4/64"	<b>DL306</b>	<b>20.15</b>	20	60
3-4/64"	3-24/64"	<b>DL328</b>	<b>21.30</b>	20	60
3-16/64"	3-32/64"	<b>DL350</b>	<b>20.50</b>	20	60


Hose OD		Plated Iron		Opt Qty	Torque in ft. lbs.
from	to	Part #	Price/E		
3-32/64"	3-52/64"	<b>400</b>	<b>\$21.00</b>	25	40
3-50/64"	4-4/64"	<b>431</b>	<b>25.10</b>	20	40
4-2/64"	4-18/64"	<b>463</b>	<b>22.95</b>	20	40
4-16/64"	4-60/64"	<b>525</b>	<b>26.70</b>	10	60
4-32/64"	5-16/64"	<b>550</b>	<b>29.00</b>	10	60
5-8/64"	5-44/64"	<b>600</b>	<b>31.55</b>	10	60
5-44/64"	5-60/64"	<b>639</b>	<b>35.15</b>	10	60
5-60/64"	6-32/64"	<b>675</b>	<b>34.15</b>	10	60
6-32/64"	7-36/64"	<b>769</b>	<b>38.10</b>	10	60
7-44/64"	8-12/64"	<b>818</b>	<b>54.40</b>	5	125
8-16/64"	8-56/64"	<b>875</b>	<b>53.80</b>	5	125
8-60/64"	9-56/64"	<b>988</b>	<b>65.60</b>	5	125
9-60/64"	11-24/64"	<b>1125</b>	<b>99.00</b>	5	125
11-12/64"	13"	<b>1275</b>	<b>110.20</b>	3	125
12-12/64"	14"	<b>1360</b>	<b>175.00</b>	2	200
13-12/64"	15"	<b>1450</b>	<b>173.50</b>	2	200
15-4/64"	17-32/64"	<b>1700</b>	<b>208.10</b>	2	260

<sup>1</sup> investment cast carbon steel

K

## Single Bolt Clamps

### Features:

- measure hose OD accurately before ordering clamps
- Torque values for clamps are based on dry bolts.
- The use of lubricant on bolts will adversely effect clamp performance. 



Hose OD		Plated Iron		Torque in ft. lbs.
from	to	Part #	Price/E	
56/64"	1"	<b>2</b>	<b>\$18.70</b>	6
62/64"	1-8/64"	<b>3</b>	<b>19.90</b>	6
1-4/64"	1-12/64"	<b>4</b>	<b>20.00</b>	6
1-10/64"	1-16/64"	<b>5</b>	<b>19.40</b>	6
1-16/64"	1-24/64"	<b>6</b>	<b>19.80</b>	6
1-22/64"	1-28/64"	<b>7</b>	<b>21.00</b>	6
1-28/64"	1-36/64"	<b>8</b>	<b>25.00</b>	6
1-34/64"	1-44/64"	<b>9</b>	<b>21.50</b>	6
1-42/64"	1-48/64"	<b>10</b>	<b>21.00</b>	6
1-48/64"	1-56/64"	<b>11</b>	<b>23.50</b>	6
1-56/64"	2-2/64"	<b>12</b>	<b>22.15</b>	6
2"	2-8/64"	<b>13</b>	<b>24.10</b>	12
2-8/64"	2-18/64"	<b>14</b>	<b>25.65</b>	12
2-16/64"	2-26/64"	<b>15</b>	<b>29.90</b>	12

Hose OD		Plated Iron		Torque in ft. lbs.
from	to	Part #	Price/E	
2-24/64"	2-32/64"	<b>16</b>	<b>\$23.60</b>	12
2-32/64"	2-40/64"	<b>17</b>	<b>23.60</b>	12
2-40/64"	2-56/64"	<b>18</b>	<b>28.75</b>	12
2-56/64"	3-4/64"	<b>19</b>	<b>27.65</b>	12
3-4/64"	3-16/64"	<b>20</b>	<b>27.00</b>	12
3-16/64"	3-28/64"	<b>21</b>	<b>30.85</b>	12
3-28/64"	3-40/64"	<b>22</b>	<b>29.50</b>	21
3-40/64"	3-52/64"	<b>23</b>	<b>40.00</b>	21
3-52/64"	4-8/64"	<b>24</b>	<b>36.80</b>	21
4-8/64"	4-20/64"	<b>25</b>	<b>38.45</b>	21
4-16/64"	4-32/64"	<b>26</b>	<b>38.70</b>	21
4-28/64"	4-40/64"	<b>27</b>	<b>45.80</b>	21
4-40/64"	4-56/64"	<b>X27</b>	<b>40.00</b>	21
4-56/64"	5-16/64"	<b>28</b>	<b>44.75</b>	21