



DURACELL®



PROFESSIONAL PRODUCTS

DURACELL® PROCELL® BATTERIES FOR PROFESSIONAL APPLICATIONS

When it comes to the workplace, we at Duracell recognize that professionals demand dependable, long lasting performance. That's why we offer DURACELL® PROCELL® professional batteries. A full line of DURACELL PROCELL alkaline, zinc air, lithium, and specialty batteries is available and is priced and packaged exclusively for professional applications. In addition to batteries, a complete selection of professional flashlights is also available covering most business needs.



DURACELL PROCELL BATTERIES

All DURACELL PROCELL batteries are manufactured to rigorous specifications to meet the high standards of durability and longevity professional users expect. All DURACELL PROCELL products are backed by Duracell's guarantee of quality and workmanship.

WHY DO DURACELL PROCELL BATTERIES LAST SO LONG?

Duracell conducts extensive testing and analysis of battery usage patterns to determine the factors having the greatest impact on battery performance. These efforts have resulted in the development of our longest lasting battery ever.

Over the last ten years a substantial investment in battery research and development has yielded significant increases in Duracell battery performance.

Duracell is committed to the development of innovations and improvements that will deliver increased customer value and satisfaction.

DURACELL... THE COMPANY BEHIND THE DURACELL PROCELL BRAND NAME

Duracell is the world's leading manufacturer and marketer of high performance alkaline batteries. In addition, Duracell markets primary lithium batteries, zinc air batteries, rechargeable nickel metal hydride batteries, and a range of specialty batteries.

DURACELL... THE BATTERY CATEGORY EXPERTS

Duracell maintains a strong commitment to grow the battery business with each of our professional customers. Every Duracell Professional Products sales team member is a battery category expert and is solely dedicated to cater to the business needs of Duracell professional customers.

CONTENTS

PAGE

DURACELL® PROCELL® PRODUCTS

ALKALINE	3
LANTERN/MEDICAL	4
ELECTRONIC	5
FLASHLIGHTS	6-7

DURACELL PRODUCTS

ULTRA	8
ALKALINE	9
LITHIUM	10
PHOTO	11
KEYLESS ENTRY/SECURITY	12
WATCH/ELECTRONIC	13
HOME MEDICAL	14
HEARING AID	15
CAMCORDER	16

MALLORY PRODUCTS

SUPER	17
-------------	----

CROSS REFERENCE	18-22
-----------------------	-------

DURACELL® PROCELL®

ALKALINE BATTERIES

DURACELL® PROCELL® alkaline batteries deliver outstanding performance and reliability. Major advantages are:

- long lasting and dependable – even after seven years of storage
- last up to ten times longer than super heavy duty zinc carbon batteries in power demanding applications
- long service life at high drain discharges
- operate reliably in temperature extremes of -20°C to 54°C
- date coded to ensure freshness
- economical bulk packaging for professional applications
- contain no added mercury



PC1300

SPECIFICATIONS	
Size/System:	Size D Alkaline
Voltage:	1.5
Max. Diameter:	1.346"
Max. Height:	2.421"
Average Weight:	4.86 oz (138.0g)
Maximum Volume:	3.44 in. ³ (56.4cm. ³)
Terminals:	Flat
Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Primary Usage:	Flashlights, Radios, Tape Recorders



PC1400

SPECIFICATIONS	
Size/System:	Size C Alkaline
Voltage:	1.5
Max. Diameter:	1.031"
Max. Height:	1.969"
Average Weight:	2.29 oz (65.0g)
Maximum Volume:	1.64 in. ³ (26.9cm. ³)
Terminals:	Flat
Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Primary Usage:	Flashlights, Radios, Tape Recorders



PC1500

SPECIFICATIONS	
Size/System:	Size AA Alkaline
Voltage:	1.5
Max. Diameter:	.571"
Max. Height:	1.988"
Average Weight:	0.83 oz (23.6g)
Maximum Volume:	0.51 in. ³ (8.4cm. ³)
Terminals:	Flat
Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Primary Usage:	Pagers, Remotes, Flashlights, Calculators



PC2400

SPECIFICATIONS	
Size/System:	Size AAA Alkaline
Voltage:	1.5
Max. Diameter:	.413"
Max. Height:	1.752"
Average Weight:	0.39 oz (11.0g)
Maximum Volume:	0.23 in. ³ (3.8cm. ³)
Terminals:	Flat
Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Primary Usage:	Pagers, Flashlights, TV Remotes



PC1604

SPECIFICATIONS	
Size/System:	9 Volt Alkaline
Voltage:	9.0
Max. Length:	.689"
Max. Width:	1.043"
Max. Height:	1.909"
Average Weight:	1.62 oz (45.9g)
Maximum Volume:	1.39 in. ³ (22.8cm. ³)
Terminals:	Miniature Snap
Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Primary Usage:	Infusion Pumps, Wireless Microphones, Smoke Alarms, Radios

DURACELL® PROCELL®

ALKALINE LANTERN BATTERIES

DURACELL® PROCELL® alkaline lantern batteries last up to twice as long as super heavy duty zinc carbon batteries and provide an extra measure of leakage resistance for critical applications. Like the popular size DURACELL PROCELL alkaline batteries, DURACELL PROCELL lantern batteries offer:

- a long shelf life
- reliable performance at temperature extremes
- date coding to ensure freshness
- bulk packaging

MEDICAL APPLICATION BATTERIES

At DURACELL® we recognize that people using batteries in the workplace have special requirements. In hospitals and healthcare facilities throughout the world, DURACELL® PROCELL® batteries keep critical electronic equipment alive and working.

PC903



SPECIFICATIONS

Size/System:	Alkaline
Voltage:	7.5
Max. Length:	7.250"
Max. Width:	4.062"
Max. Height:	3.749"
Average Weight:	78.37 oz (2,222.6g)
Average Volume:	106.0 in. ³ (1,737cm. ³)
Terminals:	Insulated Screw
Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Primary Usage:	Lanterns

PC915



SPECIFICATIONS

Size/System:	Alkaline
Voltage:	6.0
Max. Length:	2.685"
Max. Width:	2.685"
Max. Height:	PC915 4.409"
Average Weight:	21.60 oz (612g)
Average Volume:	PC915 29.20 in. ³ (478.5cm. ³)
Terminals:	PC915 Insulated Screw
Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Primary Usage:	Lanterns

DA146



SPECIFICATIONS

Size/System:	Zinc Air
Voltage:	8.4
Max. Length:	1.010"
Max. Width:	.648"
Max. Height:	1.75"
Rated Capacity:	1,300 mAh at 1,300Ω to 6.0V at 21°C (70°F)
Average Weight:	1.27 oz (36.0g)
Average Volume:	1.09 in. ³ (17.86cm. ³)
Terminals:	Miniature Snap
Operating Temperature Range:	32°F to 122°F (0°C to 50°C)
Primary Usage:	Telemetry Devices

PL1604



SPECIFICATIONS

Size/System:	Lithium-Manganese Dioxide
Voltage:	9
Max. Length:	26.4mm
Max. Width:	17.1mm
Max. Height:	48.8mm
Rated Capacity:	1.2Ah at 900 Ohm to 5.4V
Average Weight:	1.2 oz (34gm)
Average Volume:	1.3 in. ³ (21.4cm. ³)
Terminals:	Miniature Snap
Operating Temperature Range:	-4°F to 140°F (-20°C to 60°C)
Primary Usage:	Bone Growth Stimulators, Wireless Alarms, Handheld Scanners

DURACELL® PROCELL®

ELECTRONIC BATTERIES

DURACELL® PROCELL® electronic batteries are designed specifically for medical and electronic equipment.

DURACELL PROCELL electronic batteries:

- provide optimum performance in applications such as glucose meters, pagers, penlights and TV remote controls
- are bulk packaged

PL123A



SPECIFICATIONS

Size/System:	Size 123A Lithium/Manganese Dioxide	Average Weight:	0.60 oz (17.0g)
Voltage:	3.0	Terminals:	Flat, Recessed Negative Terminal
Max. Diameter:	.669"	Operating Temperature Range:	-40°F to 140°F (-40°C to 60°C)
Max. Height:	1.358"	Primary Usage:	Photo
Rated Capacity:	1,400 mAh at 100Ω to 2.0V at 20°C (68°F)		

PC9100



SPECIFICATIONS

Size/System:	Size N Alkaline	Maximum Volume:	0.21 in. ³ (3.4cm. ³)
Voltage:	1.5	Terminals:	Flat
Max. Diameter:	.472"	Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Max. Height:	1.189"	Primary Usage:	Hearing Aids Glucose Meters, Flashlights
Rated Capacity:	800 mAh at 100Ω to 0.8V at 21°C (70°F)		
Average Weight:	0.34 oz (9.6g)		

PC7K67



SPECIFICATIONS

Size/System:	Size J Alkaline	Average Weight:	1.20 oz (34.0g)
Voltage:	6.0	Maximum Volume:	0.96 in. ³ (15.7cm. ³)
Max. Length:	.362"	Terminals:	Recessed Flat
Max. Width:	1.402"	Operating Temperature Range:	-4°F to 130°F (-20°C to 54°C)
Max. Height:	1.909"	Primary Usage:	Glucose Meters, TV Remotes
Rated Capacity:	580 mAh at 340Ω to 3.2V at 21°C (70°F)		