

15 TON PISTOL

EK1550LX, EK1550FLX



- Intelli-CRIMP® Technology includes a pressure sensor that monitors the crimping force of each crimp and provides the operator a visual and audible alert if the force is below specifications
- Automatic Retraction Stop (ARS) retracts the ram just enough to get ready for the next cycle, saving time and energy

- Accepts P-style die to crimp splices and lugs up to 1500 kcmil copper and 1250 kcmil aluminum
- Accepts Kearney PH4/P14 dies without adapter
- Crimping head rotates 350°
- Includes UA15T U Die Adapter

SPECIFICATIONS

- Crimping Force: 15 Tons (135kN)
- Length: 18-1/2" (470mm)
- Width: 3-1/8" (80mm)
- Height: 13-1/2" (343mm)
- Weight: 16.3 lbs (7.4kg)

CAPACITY

- 8 AWG –1550 kcmil Cu lugs and splices
- 8 AWG –1250 kcmil Al lugs and splices



EK1550LX - KEARNEY STYLE

CAT. NO.	DESCRIPTION
EK1550LX11	15 Ton Crimper, 120V Charger, Two 4.0 Ah Batteries
EK1550LX12	15 Ton Crimper, 12V Charger, Two 4.0 Ah Batteries
EK1550LX22	15 Ton Crimper, 230V Charger, Two 4.0 Ah Batteries
EK1550LXB	Crimper, 15T Li-ion, STD, Bare Tool Only

EK1550FLX - FLIP TOP STYLE

CAT. NO.	DESCRIPTION
EK1550FLX11	15 Ton Crimper, 120V Charger, Two 4.0 Ah Batteries
EK1550FLX12	15 Ton Crimper, 12V Charger, Two 4.0 Ah Batteries
EK1550FLX22	15 Ton Crimper, 230V Charger, Two 4.0 Ah Batteries
EK1550FLXB	Crimper Flip T, 15T Li-ion, STD, Bare Tool Only

ACCESSORIES

CAT. NO.	DESCRIPTION
05167	18V 4.0Ah Li-ion Battery
52178	120V Li-ion Battery Charger
52179	230V Li-ion Battery Charger
52180	12V Li-ion Battery Charger
12274	Carrying Strap
23492	Handle
UA15T	Die Adapters – Greenlee® "U" style dies, Burndy® "U" style dies, ILSCO® ILD style dies, T&B® 15500 style dies, Blackburn® 15500 style dies
48820	Die Adapters – Burndy® P dies (Y46), ILSCO® ILD-P dies
48788	Die Adapters – T&B® 15600 dies, Blackburn® 15600 dies
48802	Die Adapters – Greenlee® 12-Ton dies, Burndy® 12-Ton dies, ILSCO® ILD dies, T&B® 15500 dies, Blackburn® 15500 dies
48824	Die Adapters – Kearney PH2/WH2