

EZ6RIC


6" Universal IC Remodel Housing with **Loose Socket and Quick Connectors**

LAMP WATTAGE: (1) MAXIMUM 75W R/PAR30, 60W A19, 65W BR30



DESIGNED FOR 2" X 8" JOIST CONSTRUCTION





DESCRIPTION

Thermally protected, IC rated specification grade remodel recessed housing. For remodeling installations where housing will be in direct contact with insulation. For fast and easy installation in existing plaster or mechanical ceilings from ½" to 1-3/8" thick. Four remodel clips are easily retractable for fixture removal if necessary. Junction box is provided with eight ½" KOs and four Romex knockouts with strain relief. Accommodates up to 75W PAR30, BR30, and A19 lamps.

SPECIFICATION


A. HOUSING - Die-formed, all aluminum construction for maximum heat dissipation and rust protection.

B. SOCKET - Medium base screw shell porcelain socket that attaches directly to the AF_series trims.

C. INSTALLATION - Four preinstalled spring clips which secure the housing firmly into ceiling to accommodate different ceiling thicknesses from ½" to 1-3/8".

D. JUNCTION BOX - UL and ETL listed for throughbranch circuit wiring, provided with eight ½" KOs and four Romex knockouts with strain relief.

E. THERMAL PROTECTION - Standard thermal protection device guards against improper installation, overlamping and misuse of insulation material.



BEAM DIA. MEASURED AT 50% OF NADIR F.C.

FEATURES

- Thermally Protected remodel IC housing.
- · Dependable, favorable design and effortless installa-
- Unit slips through 6-1/2" ceiling opening.
- · Four preinstalled spring clips which secure the housing firmly into ceiling to accommodate different ceiling thickness from 1/2" to 1-3/8".
- · Can be installed from below the ceiling.
- 7-1/4" height allows use in 2" x 8" joist construction.
- · Wire through junction box.
- · Preinstalled socket cap provides electrical contact protection against dust, paint and over spray.

OPTIONS AIR-SHUT

- · Gasket to prevent air flow from heated or air conditioned spaces.
- . Meets all national air flow requirements.

UL AND C-UL/ETL AND C-ETL LISTED

- For Damp location
- For Feed-through wiring
- For Direct contact with insulation







ITEM SELECTOR: (Please check the boxes below for the option desired)

ТҮРЕ	TRIM TYPE			BAFFLE	REFLECTOR	TRIM/RING
EZ6RIC-AT	☐ AF631	☐ AF601	☐ AF605L	□ W	□ CL	□ WH
	☐ AF649	☐ AF605	☐ AF606L	□ P	□ RG	□ BK
	□ AF630	□ AF606	□ AF633	□ SN	□ W	□ SN
	☐ AF651	□ AF636	□ B602	□ CP	□ MB	□ CP
	□ AF637	☐ AF635	□ B609	□ BZ	□ BZ	□ CH
	□ AF640	□ AF642	□ B663		□ CP	□ PB
	□ AF634	☐ AF641	□ B673		□ SN	□ BZ
	☐ AF632	☐ AF643			□ SHZ	
	□ AF644	□ AF638				
	□ AF639	☐ AF601L				

Specifications:

EZ6RIC-AT BAFFLE REFLECTOR TRIM/RING

Sample of Catalog Number: EZ6RIC-AT-AF631-W-WH



*For custom baffle, reflector, trim ring, glass color and lens options, please consult factory



6" EZ SERIES Incandescent Trims

(LAMP WATTAGE: (1) MAXIMUM 75W R/PAR30, 60W A19, 65W BR30)

Catalog Number:	
Project Name:	Туре:
Note:	elit és le a la la c

AF641RG-WH (SOCKET SUPPORTING) **REFLECTOR W/ ALBALITE LENS**














TRIM/RING FINISH:

WH, BK, SN, CP, CH, PB, BZ



AF638W-WH (SOCKET SUPPORTING) **BAFFLE W/ DROP OPAL LENS**








AF601L (SOCKET SUPPORTING) PLASTIC ALBALITE SHOWER TRIM



LENS: ALBALITE TRIM/RING FINISH:



AF605L (SOCKET SUPPORTING) PLASTIC FRESNEL SHOWER TRIM



LENS:







AF606L (SOCKET SUPPORTING) PLASTIC DROP OPAL SHOWER TRIM

AF643RG-WH (SOCKET SUPPORTING)

REFLECTOR W/ DROP OPAL LENS




DROP OPAI TRIM/RING FINISH: WHITE PLASTIC

LENS:




AF633CP **SOCKET SUPPORTING R/PAR30 OPEN TRIM**








TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ



B609W-WH REGRESSED EYEBALL WITH BAFFLE



BAFFLE FINISH: W. P. SN. CP. BZ TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ




EYEBALL FINISH: WH, BK, SN, CP, CH, PB, BZ

B663PB **PAR30 GIMBAL RING**



TRIM/RING FINISH: WH, BK, SN, CP, CH, PB. BZ




B673W-WH PAR30 BAFFLE W/ GIMBAL RING



BAFFLE FINISH: W. P. SN. CP. BZ

TRIM/RING FINISH: WH, BK, SN, CP, CH, PB, BZ



В	BAFFLE		REFLECTOR		TRIM RING	
V	V	White	CL	Chrome	WH	White
P	•	Black	RG	Gold	BK	Black
S	N	Satin Nickel	W	White	SN	Satin Nickel
C	P	Copper	MB	Black	CP	Copper
В	Z	Bronze	CP	Copper	CH	Chrome
			SN	Satin Nickel	PB	Polish Brass
					BZ	Bronze

*For custom baffle, reflector, trim ring, glass color and lens options, please consult factory.