

ACSR CUTTERS

ESG45LX, ESG55LX



ESG45LX

- Designed specifically to cut ACSR, guy strand and ground rods
- Retraction Stop allows the operator to stop the ram retraction at any point simply by tapping the trigger, and then starting the next cutting cycle from that point saving time and energy
- Two-stage hydraulic system provides fast advance and power speeds
- One trigger controls all tool functions
- Cutting head rotates 350°
- Tools automatically retract when the cutting cycle is complete



SPECIFICATIONS

- Width: 4" (101mm)
- Height: 20" (508mm)
- Weight: 10 lbs (4.5kg)

CAPACITY

- ACSR: 1590 kcmil
- Standard Guy Strand: 5/8" diameter (16mm)
- EHS Guy Strand: 1/2" diameter (13mm)

ESG45LX

CAT. NO.	DESCRIPTION
ESG45LX11	45mm ACSR Cutter, 120V Charger, Two 4.0 Ah Batteries
ESG45LX12	45mm ACSR Cutter, 12V Charger, Two 4.0 Ah Batteries
ESG45LX22	45mm ACSR Cutter, 230V Charger, Two 4.0 Ah Batteries
ESG45LXB	45mm ACSR Cutter, Bare Tool Only

ACCESSORIES

CAT. NO.	DESCRIPTION
05167	18V 4.0Ah Li-ion Battery
52178	120V Li-ion Battery Charger
52179	230V Li-ion Battery Charger
52180	12V Li-ion Battery Charger
12274	Carrying Strap



ESG55LX



- Lightweight and very easy to handle
- One trigger controls all tool functions
- Cutting head rotates 350°
- Tools automatically retract when the cutting cycle is complete

SPECIFICATIONS

- Length: 18-1/8" (460mm)
- Width: 3-1/8" (80mm)
- Height: 13-1/4" (337mm)
- Weight: 17.5 lbs (8kg)

CAPACITY

- ACSR: 2515 Kcmil
- Standard Guy Strand: 5/8" diameter (16mm)
- EHS Guy Strand: 9/16" diameter (14mm)

ESG55LX

CAT. NO.	DESCRIPTION
ESG55LX11	55mm ACSR Cutter, 120V Charger, Two 4.0 Ah Batteries
ESG55LX12	55mm ACSR Cutter, 12V Charger, Two 4.0 Ah Batteries
ESG55LX22	55mm ACSR Cutter, 230V Charger, Two 4.0 Ah Batteries
ESG55LXB	55mm ACSR Cutter, Bare Tool Only