



Engineer's Hammer

with PATENTED End Cap



Order Number	UPC Number	Head Weight approx. oz./grams	Overall Length approx. in./mm	Shelf Pack	Master Pack	Weight lbs/kilos
E6-48E	0 34139 62031 0	48 oz / 1344 g	16" / 406 mm	4	12	36 lbs / 16.2 kg

Lineman's Hammer



Order Number	UPC Number	Head Weight approx. oz./grams	Overall Length approx. in./mm	Shelf Pack	Master Pack	Weight lbs/kilos
E3-40L	0 34139 62991 7	40 oz / 1134 g	13.5" / 343 mm	4	24	62 lbs / 27.9 kg

Ballpeen Hammers



Order Number	UPC Number	Head Weight approx. oz./grams	Overall Length approx. in./mm	Shelf Pack	Master Pack	Weight lbs/kilos
E3-8BP	0 34139 62311 3	8 oz / 224 g	11" / 279 mm	2	48	54 lbs / 24.3 kg
E3-12BP	0 34139 62331 1	12 oz / 336 g	11" / 279 mm	4	48	63 lbs / 28.4 kg
E3-16BP	0 34139 62341 0	16 oz / 448 g	13" / 330 mm	2	24	43 lbs / 19.4 kg
E3-24BP	0 34139 62781 4	24 oz / 672 g	13.5" / 343 mm	2	24	54 lbs / 24.3 kg
E3-32BP	0 34139 62961 0	32 oz / 896 g	14.5" / 368 mm	4	24	62 lbs / 27.9 kg

Drywall Hammers

Round Face



	Order Number	UPC Number	Head Weight approx. oz./grams	Overall Length approx. in./mm	Shelf Pack	Master Pack	Weight lbs/kilos
Milled Face	E3-11	0 34139 62221 5	11 oz / 308 g	13.5" / 343 mm	2	24	16 lbs / 7.5 kg

- Nail Hammers are for driving and withdrawing common nails only.
- Drilling Hammers are intended to be used for striking chisels, punches, star drills and hardened nails.
- Ball Peen Hammers have two separate uses. The striking face of the ball peen is used for striking punches and chisels. The ball peen end is used for riveting, shaping and straightening unhardened metals.
- Drywall Hammers are to be used for scoring and installing drywall.
- Shingler's Hatchets are to be used for installing and trimming composition, wood and fiberglass shingles.
- Bricklayer Hammers are used for setting or splitting bricks.

Unique Design and Construction Features

Estwing's first and finest solid steel hammers are unsurpassed in quality, balance and finish. Forged one-piece tool steel is the strongest construction known. Fully polished head and handle neck. All with Estwing's exclusive Shock Reduction Grip.



The World's Best Shock Reduction Grip
Permanently molded and bonded to handle.



Estwing Hammers are also available in beautiful laminated leather grips. Laminated **leather** washers are pressed on and riveted. Grip is triple laquered for a beautiful finish.

Protect Your Eyes, Wear Safety Goggles



OSHA regulations 29 CFR 1910.133 requires the use of eye protection not only for workers using striking tools, but for nearby workers in the immediate working area. Similar requirements are contained in OSHA Construction Standards 29 CFR 1926.102. Mine Safety and Health Administration requires eye protection in the Mining environment 30-CFR 55.14-4, 30 CFR 56-15-4, 30 CFR 57-15-4, 30 CFR 75.1720 (a) and 30 CFR 77.1710 (a).