




# Wrenches

## EXTRA THIN OPEN END WRENCHES -SATIN FINISH

- Satin finish provides corrosion resistance and a slip resistant grip.
- Ultra-thin profile and long handle produce improved access to hard-to-reach fasteners.
- Use when high leverage or distance from a hot assembly is required.
- Opening is designed to cover tappets, screws and lock nuts without excessive overhang which improves access.




Product ID No.	 in.	B	C	D	B1	C1	D1	L	Weight lbs.
J3425	7/16" x 1/2"	19/32"	1-3/32"	11/64"	33/64"	1-1/64"	11/64"	10"	.16
J3426	1/2" x 9/16"	43/64"	1-13/64"	11/64"	19/32"	1-9/64"	11/64"	10"	.16
J3430	9/16" x 5/8"	47/64"	1-21/64"	11/64"	43/64"	1-1/4"	11/64"	10"	.21
J3435	11/16" x 3/4"	57/64"	1-7/16"	13/64"	13/16"	1-11/32"	13/64"	10"	.26
J3440	13/16" x 7/8"	1-1/32"	1-49/64"	13/64"	31/32"	1-11/16"	13/64"	10"	.33

## CHECK NUT WRENCHES

- Use check nut wrenches to tighten jam nuts, check nuts or lock nuts.
- In confined spaces, the 15° head allows for a full 30° rotation by flipping wrench over.
- Ultra thin profile improves access in close quarters.
- Non-reflective black oxide finish for use where non-plated products are required.



Product ID No.	 in.	Head Width	Head Thickness	Length	Weight lbs.
JKE14	7/16"	1"	7/32"	4"	0.05 lbs.
JKE16	1/2"	1"	7/32"	4"	0.05 lbs.
JKE18	9/16"	1-9/32"	7/32"	4-1/2"	0.11 lbs.
JKE19	19/32"	1-9/32"	7/32"	4-1/2"	0.11 lbs.
JKE20	5/8"	1-1/2"	1/5"	5-7/32"	0.13 lbs.
JKE22	11/16"	1 1/2"	7/32"	5-7/32"	0.13 lbs.
JKE24	3/4"	1-23/32"	9/32"	6-7/32"	0.19 lbs.
JKE26	13/16"	2"	9/32"	6-23/32"	0.28 lbs.
JKE28	7/8"	1-25/32"	9/32"	6-19/32"	0.28 lbs.
JKE30	15/16"	2"	9/32"	7-1/2"	0.36 lbs.
JKE32	1"	2"	9/32"	7-1/2"	0.35 lbs.
JKE34	1-1/16"	2-13/32"	9/32"	8-1/2"	0.66 lbs.
JKE36	1-1/8"	2-13/32"	9/32"	8-1/2"	0.65 lbs.
JKE40	1-1/4"	2-23/32"	13/32"	10"	1.12 lbs.
JKE42	1-5/16"	2-23/32"	13/32"	10"	1.12 lbs.
JKE48	1-1/2"	3-7/32"	13/32"	11-19/32"	1.5 lbs.
JKE52	1-5/8"	3-1/2"	13/32"	13"	2.3 lbs.
JKE54	1-11/16"	3-7/16"	1/2"	13"	2.2 lbs.

