



GE  
Lighting

97601 - GE Ecolux® Blax® T4 - Facilities; Retail Display; Hospitality;  
Office; Restaurant; Warehouse

F18DBX/841/ECO4P

## Product Photo



### GENERAL CHARACTERISTICS

Base Type	Pin/Plug-In
Mercury Content	3 mg
Rated Life Hours-nominal	17000 h
Starting Temp (MIN) C-degrees	0 °C
Mercury-Picogram per mean lm hr	181.9
Primary Application	Facilities Retail Display Hospitality Office Restaurant Warehouse
Product Technology	Compact Fluorescent
Base	G24q-2
Bulb Shape	A19

### PHOTOMETRIC CHARACTERISTICS

Mean Lumens nominal	970 lm
Nominal Initial Lumen per Watt	69
Initial Lumens-nominal	1250 lm
Color Rendering Index-CRI	82
Color Temperature	4100 K

### PRODUCT INFORMATION

Product Code	97601
Description	F18DBX/841/ECO4P
Alternative Unit Of Measure	BUNDLE
Standard Package Quantity	50
Ean UPC	043168976015
Standard Package GTIN	
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	50
Sales Unit	Unit
UCC	043168976015

### DIMENSIONS

Base Face to Top of Lamp	5.2 in
Nominal Length	5.8 in
Bulb Max Overall Length-MOL	5.8 in

### ELECTRICAL CHARACTERISTICS

Equivalent Incandescent Watts	65 W
Current Crest Factor (MAX)	5.25
Supply Current Freq nominal Hz	60 Hz
Rated power (Watts)	18 W

### CAUTIONS & WARNINGS

#### Caution

Lamp may shatter and cause injury if broken

Remove and install by grasping only plastic portion of the lamp.

### NOTES

4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).