



## Vulcanized Rubber Tread Wheels

Load Capacity 380-1,870 lbs. Each Wheel

Cushioned rubber tread permanently vulcanized to a semi-steel core is recommended for quiet movement with heavy loads. Molded core provides added strength with a reinforced, double-thick hub. Vulcanized rubber-tread wheels are standard with roller bearings. Temperature operating range is -40°F to +158°F. Durometer rating is 75A.

Wheel Dia. (In.)	Tread Width (In.)	Load Rating (Lbs.)	Hub Length (In.)	Axle Size			Use With Swivel Caster Series	Tread Wheel Desc.	Order No.
				Without Roller Bearing	With Bearing, No Spanner	With Bearing and Spanner			
4	2	380	2 <sup>3</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>	3/4	1/2	1400	18-4x2	37810
5	2	380	2 <sup>3</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>	3/4	1/2	1400	18-5x2	37813
6	2	420	2 <sup>3</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>	3/4	1/2	H, CPA	18-6x2	37861
		770	2 <sup>1</sup> / <sub>4</sub>	1 <sup>3</sup> / <sub>16</sub>	3/4	-		18HD-6x2	61488
	2 <sup>1</sup> / <sub>2</sub>	600	2 <sup>7</sup> / <sub>8</sub>	1 <sup>3</sup> / <sub>16</sub>	3/4	1/2	H	18-6Hx2 <sup>1</sup> / <sub>2</sub>	37769
		600	3 <sup>1</sup> / <sub>4</sub>	1 <sup>15</sup> / <sub>16</sub>	1	3/4		18-6x2 <sup>1</sup> / <sub>2</sub>	37773
	3	700	3 <sup>1</sup> / <sub>4</sub>	1 <sup>15</sup> / <sub>16</sub>	1	3/4		18-6x3	37779
		1050	3 <sup>1</sup> / <sub>4</sub>	1 <sup>13</sup> / <sub>16</sub>	1	-		18HD-6x3	61489
8	2	500	2 <sup>3</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>	3/4	1/2	H, CPA	18-8x2	37891
		1000	2 <sup>1</sup> / <sub>4</sub>	1 <sup>3</sup> / <sub>16</sub>	3/4	-		18-8HDx2	61490
	2 <sup>1</sup> / <sub>2</sub>	800	2 <sup>7</sup> / <sub>8</sub>	1 <sup>3</sup> / <sub>16</sub>	3/4	1/2	H	18-8Hx2 <sup>1</sup> / <sub>2</sub>	37770
		800	3 <sup>1</sup> / <sub>4</sub>	1 <sup>15</sup> / <sub>16</sub>	1	3/4		18-8x2 <sup>1</sup> / <sub>2</sub>	37774
	3	1100	3 <sup>1</sup> / <sub>4</sub>	1 <sup>13</sup> / <sub>16</sub>	1	-		18-8HDx2 <sup>1</sup> / <sub>2</sub>	61491
		850	3 <sup>1</sup> / <sub>4</sub>	1 <sup>15</sup> / <sub>16</sub>	1	3/4		18-8x3	37780
10	2 <sup>1</sup> / <sub>2</sub>	1200	3 <sup>1</sup> / <sub>4</sub>	1 <sup>13</sup> / <sub>16</sub>	1	-		18-8HDx3	61492
		800	2 <sup>7</sup> / <sub>8</sub>	1 <sup>3</sup> / <sub>16</sub>	3/4	1/2	H	18-10Hx2 <sup>1</sup> / <sub>2</sub>	37772
	3	900	3 <sup>1</sup> / <sub>4</sub>	1 <sup>15</sup> / <sub>16</sub>	1	3/4		18-10x2 <sup>1</sup> / <sub>2</sub>	37776
		1150	3 <sup>1</sup> / <sub>4</sub>	1 <sup>13</sup> / <sub>16</sub>	1	-		18-10HDx2 <sup>1</sup> / <sub>2</sub>	61493
	3	1000	3 <sup>1</sup> / <sub>4</sub>	1 <sup>15</sup> / <sub>16</sub>	1	3/4		18-10x3	37781
		1650	3 <sup>1</sup> / <sub>4</sub>	1 <sup>13</sup> / <sub>16</sub>	1	-		18-10HDx3	61494
12	2 <sup>1</sup> / <sub>2</sub>	900	3 <sup>1</sup> / <sub>4</sub>	1 <sup>15</sup> / <sub>16</sub>	1	3/4		18-12x2 <sup>1</sup> / <sub>2</sub>	37777
		1550	3 <sup>1</sup> / <sub>4</sub>	1 <sup>13</sup> / <sub>16</sub>	1	-		18HD-12x2 <sup>1</sup> / <sub>2</sub>	61507
	3	1150	3 <sup>1</sup> / <sub>4</sub>	1 <sup>15</sup> / <sub>16</sub>	1	3/4		18-12x3	37783
		1870	3 <sup>1</sup> / <sub>4</sub>	1 <sup>13</sup> / <sub>16</sub>	1	-		18HD-12x3	61508

NOTE: Roller Bearings are standard. If spanner required, order separately.

WHEELS