

# Hazardous Environments

#### STANDARD SERIES FLASHLIGHTS



#### XPP-5420G

Safety Rating Runtime **Batteries** 

Water / Dust Rating IP-67

Class I Div 1 Groups A-D T3 14 hrs

#### XPP-5422G

Safety Rating Runtime **Batteries** 

Class I Div 1 Groups A-D T3 17.5 hrs





XPP-5422GM

. C E ECE EX X MSHA

Class I Div 1 Groups A-D T3 Safety Rating Runtime 17.5 hrs 3 AA Water / Dust Rating IP-67



#### X-SERIES FLASHLIGHTS



#### XPP-5420GX

Safety Rating Class I Div 1 Groups A-D T3


Runtime Batteries Water / Dust Rating IP-67



## XPP-5422GX

Class I Div 1 Groups A-D T3 Safety Rating Runtime

14 hrs Water / Dust Rating IP-67





XPP-5422GMX

. ( C E KKK (Ex)

Safety Rating Runtime **Batteries** 

Class I Div 1 Groups A-D T3 14 hrs Water / Dust Rating IP-67



#### **PENLIGHTS**



#### Safety Rating

Class I Div 1 Groups A-D T3

Runtime 2 AAA **Batteries** Water / Dust Rating IP-67



Safety Rating Runtime

Class I Div 1 Groups A-D T3 13.75 hrs 3 AAAA

**Batteries** Water / Dust Rating IP-67

THE NIGHTSTICK DIFFERENCE

Nightstick, designed and manufactured by Bayco Products, Inc., is a global brand of professional lighting products including flashlights, headlamps and Intrinsically Safe lighting solutions that exceed the industry standards in performance, quality, user-safety and value. For over 30 years, Bayco Products, Inc. has been the preferred choice of professionals and discriminating consumers. The Nightstick and Bayco brands are recognized world-wide as high-performance. high-quality, high-value lighting solutions across virtually every industry. Headquartered in North Texas, Bayco Products' 110,000 square foot facility is the international headquarters for R&D, engineering, marketing, sales and distribution. Bayco Products has dedicated ISO 9001 Certifed factories both in the US and abroad. www.nightstick.com

#### **HEADLAMPS**



XPP-5450G

. ( ) [ECEX (EX) ] NAME TO (

Safety Rating Runtime Water / Dust Rating

Class I Div 1 Groups A-D T3 13.5 hrs 3 AAA



XPP-5452G

. C E E E E E Safety Rating Class I Div 1 Groups A-D T3


Runtime 4.5 hrs 3 AAA **Batteries** Water / Dust Rating IP-67





Class I Div 1 Groups A-D T3 Runtime 5 hrs Batteries

3 AAA Water / Dust Rating IP-67





XPP-5456G

Class I Div 1 Groups A-D T3 Safety Rating **Batteries** 3 AA

Water / Dust Rating IP-67




XPP-5458G

Safety Rating

Class I Div 1 Groups A-D T3

Runtime **Batteries** Water / Dust Rating IP-67





XPP-5460GX

Class I Div 1 Groups A-D T4 Safety Rating Runtime 3.5 hrs 3 AAA Water / Dust Rating IP-67



XPP-5462GX Safety Rating

Class I Div 1 Groups A-D T4

Runtime **Batteries** Water / Dust Rating IP-67

## RECHARGEABLE FLASHLIGHTS



Safety Rating Class I Div 1 Groups A-D T3 Runtime 8 hrs **Batteries** 

Rechargeable Li-ion IP-67

Water / Dust Rating



Safety Rating Class I Div 1 Groups A-D T3 9.5 hrs

Rechargeable Li-ion Water / Dust Rating IP-67



#### ZERO BAND HEADLAMPS



XPP-5450GC

. C E E E

Safety Rating Runtime Water / Dust Rating IP-67

Class I Div 1 Groups A-D T3 13.5 hrs





4.5 hrs

3 AAA

XPP-5452GC

Safety Rating

.**..... ( 6 🚾** 🐼

Water / Dust Rating IP-67

Runtime

Class I Div 1 Groups A-D T3





**XPP-5454GC** 

Safety Rating

Runtime

. C E E E E Z Class I Div 1 Groups A-D T3

3 AAA Water / Dust Rating IP-67

5 hrs







XPP-5460GCX

Safety Rating

Runtime

**Batteries** 

Class I Div 1 Groups A-D T4 3.5 hrs 3 AAA Water / Dust Rating IP-67

ULus C € ECEX EX

#### HELMET-MOUNTED FLASHLIGHT



Class I Div 1 Groups A-D T4 Safety Rating Runtime **Batteries** 2 CR-123 Water / Dust Rating IP-67



#### **ANGLE LIGHTS**

XPP-5570GA

Water / Dust Rating IP-67

XPR-5572GA

Water / Dust Rating IP-67

Safety Rating Runtime

Safety Rating

Runtime **Batteries** 



Available in Red

. C € KEX EX MSHA

Class I Div 1 Groups A-D T3



21 hrs

Available in Red

. C E Ex MSHA Class I Div 1 Groups A-D T3

## RECHARGEABLE LANTERN

Rechargeable Li-ion



Class I Div 1 Groups A-D T3 Safety Rating Runtime 9.25 hrs Rechargeable Li-ion **Batteries** Water / Dust Rating IP-67

STANDARD SERIES FLASHLIGHTS	Part Number	Dual-Light	Multi-Function	Lumens	Run-time (hrs)	Beam Distance	Candela	Water Rating	Case Material	Power Source	Warranty	Certification
	XPP-5420G			140	14	180 m	7,500	Waterproof	Polymer	3 AA (not included)	Limited Lifetime	Class I Div 1 Grps A-D T3, Class II & III Div 1 Grps E-G T3, Class I Zone 0 AEx ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, I M1 Ex ia I Ma, II 1 G Ex ia IIC T3 Ga, Ex ia I Ma, Ex ia II C T3 Ga, MSHA: CRF 30 Part 20 Class 1, InMetro: Ex ia I Ma, Ex ia IIC T3 Ga (-20°C   5 Tamb \$\xi\$ +40°C)
	XPP-5422G	Yes	Yes	120 / 120 / 240	17.5 / 17.5 / 4.5	170 m	7,250	Waterproof	Polymer	3 AA (not included)	Limited Lifetime	Class I Div 1 Grps A-D T3, Class II & III Div 1 Grps E-G T3, Class I Zone 0 AEx ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, I M1 Ex ia I Ma, II 1 G Ex ia IIC T3 Ga, Ex ia I Ma, Ex ia IIC T3 Ga, MSHA: CRF 30 Part 20 Class 1, InMetro: Ex ia I Ma, Ex ia IIC T3 Ga (-20°C ≤ Tamb ≤ +40°C)
	XPP-5422GM	Yes	Yes	120 / 120 / 240	17.5 / 17.5 / 4.5	170 m	7,250	Waterproof	Polymer	3 AA (not included)	Limited Lifetime	Class I Div 1 Grps A-D T3, Class II & III Div 1 Grps E-G T3, Class I Zone 0 AEx ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, I M1 Ex ia I Ma, II 1 G Ex ia IIC T3 Ga, Ex ia I Ma, Ex ia IIC T3 Ga, MSHA: CRF 30 Part 20 Class 1, InMetro: Ex ia I Ma, Ex ia IIC T3 Ga (-20°C ≤ Tamb ≤ +40°C)
X-SERIES FLASHLIGHTS	Part Number	Dual-Light	Multi-Function	Lumens	Run-time (hrs)	Beam Distance	Candela	Water Rating	Case Material	Power Source	Warranty	Certification
28-31-76E 7-6	XPP-5420GX			210	14	187 m	7970	Waterproof	Polymer	3 AA (not included)	Limited Lifetime	Class I Div 1 Grps A-D T3; Class II & III Div 1 Grps E-G T3; Class I Zone 0 AEx ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, I M1 Ex ia op is I Ma, II 1 G Ex ia op is IIC T3 Ga, Ex ia op is I Ma, Ex ia op is IIC T3 Ga
THE ARMST THE STATE OF THE STAT	XPP-5422GX	Yes	Yes	210 / 130 / 285	14 / 20 / 10	187 m	7970	Waterproof	Polymer	3 AA (not included)	Limited Lifetime	Class I Div 1 Grps A-D T3; Class II & III Div 1 Grps E-G T3; Class I Zone 0 AEx ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, I M1 Ex ia op is I Ma, II 1 G Ex ia op is IIC T3 Ga, Ex ia op is I Ma, Ex ia op is IIC T3 Ga
	XPP-5422GMX	Yes	Yes	210 / 130 / 285	14 / 20 / 10	187 m	7970	Waterproof	Polymer	3 AA (not included)	Limited Lifetime	Class I Div 1 Grps A-D T3; Class II & III Div 1 Grps E-G T3; Class I Zone 0 AEx ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, I M1 Ex ia op is I Ma, II 1 G Ex ia op is IIC T3 Ga, Ex ia op is I Ma, Ex ia op is IIC T3 Ga
PENLIGHTS	Part Number	Dual-Light	Multi-Function	Lumens	Run-time (hrs)	Beam Distance	Candela	Water Rating	Case Material	Power Source	Warranty	Certification
<b>4 - - - -</b>	XPP-5410G			30	18	40 m	107	Waterproof	Polymer	2 AAA	Limited Lifetime	Class I Div 1 Grps A-D T3; Class II & III Div 1 Grps E-G T3; Class I Zone 0 AEx ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, I M1 Ex ia op is I Ma, II 1 G Ex ia op is IIC T3 Ga, Ex ia op is I Ma, Ex ia op is IIC T3 Ga, MSHA: CRF 30 Part 20 Class 1, InMetro: Ex ia op is I Ma, Ex ia op is IIC T3 Ga (-20°C ≤ Tamb ≤ +40°C)
	XPP-5412G			50	13.75	50 m	161	Waterproof	Polymer	3 AAAA	Limited Lifetime	Class I Div 1 Grps A-D T3: Class II & III Div 1 Grps E-G T3; Class I Zone 0 AEx ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, I M1 Ex ia op is I Ma, II 1 G Ex ia op is IIC T3 Ga, Ex ia op is I Ma, Ex ia op is IIC T3 Ga
HEADLAMPS	Part Number	Dual-Light	Multi-Function	Lumens	Run-time (hrs)	Beam Distance	Candela	Water Rating	Case Material	Power Source	Warranty	Certification
- Annual Section 1	XPP-5450G		Yes	60 / 40	13.5 / 22.75	80 / 65 m	1,615 / 1,076	Waterproof	Polymer	3 AAA	Limited Lifetime	Class I Div 1 Grps A-D T3, Class II & III Grps E-G T135°C, Class I Zone 0 Aex ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, II 1 G Ex ia op is IIC T3 Ga, Ex ia IIC T3 Ga
Name of the second	XPP-5452G		Yes	115 / 65	4.5 / 13	92 / 67 m	2,152 / 1,141	Waterproof	Polymer	3 AAA	Limited Lifetime	Class I Div 1 Grps A-D T3, Class II & III Grps E-G T135°C, Class I Zone 0 Aex ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, II 1 G Ex ia op is IIC T3 Ga, Ex ia IIC T3 Ga
	XPP-5454G	Yes	Yes	115 / 60 / 120 / 60 / 160	5 / 16.25 / 5.25 / 16.75 / 3.5	82 / 60 m	1,668 / 882	Waterproof	Polymer	3 AAA	Limited Lifetime	Class I Div 1 Grps A-D T3, Class II & III Grps E-G T135°C, Class I Zone 0 Aex ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, II 1 G Ex ia IIC T3 Ga, Ex ia IIC T3 Ga, InMetro: Ex ia IIC T3 Ga (-20°C ≤ Tamb ≤ +40°C)
	XPP-5456G	Yes	Yes	100 / 90 / 20 / 18 / 175	18 / 13.5 / 75 / 37 / 6.5	140 m	4,820	Waterproof	Polymer	3 AA	Limited Lifetime	Class I Div 1 Grps A-D T3, Class II & III Grps E-G T135°C, Class I Zone 0 Aex ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, I M1 Ex ia I Ma, II 1 G Ex ia IIC T3 Ga, Ex ia I Ma, Ex ia IIC T3 Ga, MSHA: CRF 30 Part 20 Class 1
	XPP-5458G	Yes	Yes	130 / 100 / 25 / 21 / 190	14 / 12.5 / 70 / 37 / 6	120 m	3,500	Waterproof	Polymer	3 AA	Limited Lifetime	Class I Div 1 Grps A-D T3, Class II & III Grps E-G T135°C, Class I Zone 0 Aex ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, I M1 Ex ia I Ma, II 1 G Ex ia IIC T3 Ga, Ex ia I Ma, Ex ia IIC T3 Ga, MSHA: CRF 30 Part 20 Class 1
	XPP-5460GX	Yes	Yes	180 / 100 / 180 / 100 / 200	3.5 / 9.75 / 2.75 / 10.5 / 2.75	106 m	2,799	Waterproof	Glass-Filled Nylon Polymer	3 AAA	Limited Lifetime	Class I Div 1 Grps A-D T4; Class II & III Div 1 Grps E-G T135°C; Class I Zone 0 AEx ia IIC T4 Ga, Class I Zone 0 Ex ia IIC T4 Ga, II 1 G Ex ia IIC T4 Ga, Ex ia IIC T4 Ga
- The second	XPP-5462GX	Yes	Yes	275 / 100 / 250 / 100 / 310	6.75 / 27.75 / 6.25 / 20.25 / 6	120 m	3,660	Waterproof	Glass-Filled Nylon Polymer	3 AA	Limited Lifetime	Class I Div 1 Grps A-D T4; Class II & III Div 1 Grps E-G T135°C; Class I Zone 0 AEx ia IIC T4 Ga, Class I Zone 0 Ex ia IIC T4 Ga, II 1 G Ex ia IIC T4 Ga, Ex ia IIC T4 Ga
RECHARGEABLE FLASHLIGHTS	Part Number	Dual-Light	Multi-Function	Lumens	Run-time (hrs)	Beam Distance	Candela	Water Rating	Case Material	Power Source	Warranty	Certification
	XPR-5522GMX	Yes		240 / 175 / 400	8	150 m	5,381	Waterproof	Polymer	Rechargeable Lithium-ion	Limited Lifetime	Class I Div 1 Grps A-D T3; Class II Div 1 Grps E-G T3; Class III Div 1 T165°C; Class I Zone 0 AEx ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, II 1 G Ex ia op is IIC T3 Ga, Ex ia op is IIC T3 Ga, MSHA: CRF 30 Part 20 Class 1
	XPR-5542GMX	Yes	Yes	260 / 200 / 150	9.5 / 8 / 4	147 m	5,430	Waterproof	Glass-Filled Nylon Polymer	Rechargeable Lithium-ion	Limited Lifetime	Class I Div 1 Grps A-D T3; Class II & III Div 1 Grps E-G T135°C; Class I Zone 0 AEx ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, II 1 G Ex ia IIC T3 Ga, Ex ia IIC T3 Ga
ZERO BAND SERIES	Part Number	Dual-Light	Multi-Function	Lumens	Run-time (hrs)	Beam Distance	Candela	Water Rating	Case Material	Power Source	Warranty	Certification
<b>*</b> (a) (b)	XPP-5450GC		Yes	60 / 40	13.5 / 22.75	80 / 65 m	1,615 / 1,076	Waterproof	Polymer	3 AAA	Limited Lifetime	Class I Div 1 Grps A-D T3, Class II & III Grps E-G T135°C, Class I Zone 0 Aex ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, II 1 G Ex ia op is IIC T3 Ga, Ex ia IIC T3 Ga
<b>*</b> (a) (b)	XPP-5452GC		Yes	115 / 65	4.5 / 13	92 / 67 m	2,152 / 1,141	Waterproof	Polymer	3 AAA	Limited Lifetime	Class I Div 1 Grps A-D T3, Class II & III Grps E-G T135°C, Class I Zone 0 Aex ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, II 1 G Ex ia op is IIC T3 Ga, Ex ia IIC T3 Ga
<b>*</b> 6 9	XPP-5454GC	Yes	Yes	115 / 60 / 120 / 60 / 160	5 / 16.25 / 5.25 / 16.75 / 3.5	82 / 60 m	1,668 / 882	Waterproof	Polymer	3 AAA	Limited Lifetime	Class I Div 1 Grps A-D T3, Class II & III Grps E-G T135°C, Class I Zone 0 Aex ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, II 1 G Ex ia IIC T3 Ga, Ex ia IIC T3 Ga, InMetro: Ex ia IIC T3 Ga (-20°C ≤ Tamb ≤ +40°C)
<b>*</b> • •	XPP-5460GCX	Yes	Yes	180 / 100 / 180 / 100 / 200	3.5 / 9.75 / 2.75 / 10.5 / 2.75	106 m	2,799	Waterproof	Glass-Filled Nylon Polymer	3 AAA	Limited Lifetime	Class I Div 1 Grps A-D T4; Class II & III Div 1 Grps E-G T135°C; Class I Zone 0 AEx ia IIC T4 Ga, Class I Zone 0 Ex ia IIC T4 Ga, II 1 G Ex ia IIC T4 Ga, Ex ia IIC T4 Ga
HELMET-MOUNTED FLASHLIGHT	Part Number	Dual-Light	Multi-Function	Lumens	Run-time (hrs)	Beam Distance	Candela	Water Rating	Case Material	Power Source	Warranty	Certification
\$	XPP-5466G	Yes	Yes	250 / 100 / 20 135 / 50 / 15 / 125	2.5 / 10 / 30 2.5 / 21 / 60 / 3.25	208 m	10,800	Waterproof	ADC12 Aluminum Alloy	2 CR-123	Limited Lifetime	Class I Div 1 Grps A-D T4; Class II & III Div 1 Grps E-G T135°C; Class I Zone 0 AEx ia IIC T4 Ga, Class I Zone 0 Ex ia IIC T4
ANGLE LIGHTS	Part Number	Dual-Light	Multi-Function	Lumens	Run-time (hrs)	Beam Distance	Candela	Water Rating	Case Material	Power Source	Warranty	Certification
•	XPP-5570GA	Yes	Yes	200 / 100 / 60 200 / 100 / 20 /	21 / 42 / 84 21 / 42 / 84	267 m 199 m	22,249 14,828	Waterproof	Glass-Filled Nylon Polymer	6 AA	Limited Lifetime	Class I Div 1 Grps A-D T4, Class II & III Div 1 Grps E-G T135°C, Class I Zone 1 AEx ia IIC T4 Gb, Class II Zone 20 IIIC, Ex ia IIC T4 Gb, II 1 G Ex ia IIC T4 Gb, Ex ia IIC T4
	XPR-5572GA	Yes	Yes	200 200 / 100 / 60 200 / 100 / 20 /	21 6 / 11.5 / 22.5 6 / 11.5 / 30	145 m 267 m 199 m	7,790 22,249 14,828	Waterproof	Glass-Filled	Rechargeable Lithium-ion	Limited Lifetime	Gb, MSHA: CRF 30 Part 20 Class 1  Class I Div 1 Grps A-D T4, Class II & III Div 1 Grps E-G T135°C, Class I Zone 1 AEx ia IIC T4 Gb, Class II Zone 20 IIIC, Ex ia IIC T4 Gb, II 1 G Ex ia IIC T4 Gb, Ex ia IIC T4
-				200	6	145 m	7,790	p. 001	Nylon Polymer  Glass-Filled	(or 6 AA)		Gb, MSHA: CRF 30 Part 20 Class 1
1	5572-BASE					- XIII BO A			Nylon Polymer		2 Year Limited	

#### **TESTING LABORATORIES**

XPR-5580G



RECHARGEABLE LANTERN

> The ETL Listed Mark is proof of product compliance (electrical, gas and other safety standards) to North American safety standards, including UL, ANSI, CSA, ASTM and NFPA standards.

210 / 100 / 30 210 / 100 / 30

101,000 16,515 6,705

Waterproof

Nylon Polymer



cULus

ETL

The cULus Listed Mark indicates products have been evaluated and are in compliance with both Canadian and U.S. safety



requirements. **ATEX Directive** The European based ATEX directive defines the equipment and work environment that is allowed to function in an explosive

atmosphere. The regulations apply to all equipment intended for



use in explosive atmospheres, either electrical or mechanical, including protective systems. CE CE CE mark is the official marking required by the European Community for products that will be sold, or put into sensiti



Community for products that will be sold, or put into service in the European community. The product fulfills all essential safety and environmental requirements for the product's intended use, as they are defined in the European Directives, primarily ISO Standards. **IECEx** 



The IECEx is the International Electrotechnical Commission system for the certification to standards for electrical equipment for explosive atmospheres.



Mine Safety and Health Administration requires that portable

battery operated lighting be designed and tested to not pose an explosion hazard in mining operations.



**INMETRO** 

National Institute of Metrology, Quality and Technology (Inmetro) supports Brazilian enterprises, to increase their productivity and the quality of goods and services.

CERTIFICATION CHART	o us Intertek	c UL Us	€x>	CE	IECEx	MSHA	INMETRO
XPP-5420G	•		<b>~</b>	<b>~</b>	<b>*</b>	<b>~</b>	<b>*</b>
XPP-5422G	<b>*</b>		~	<b>~</b>	<b>*</b>	<b>~</b>	<b>*</b>
XPP-5422GM	<b>*</b>		~	<b>~</b>	<b>*</b>	<b>~</b>	<b>*</b>
XPP-5420GX	<b>*</b>		~	<b>~</b>	<b>*</b>		
XPP-5422GX	<b>*</b>		~	<b>~</b>	<b>~</b>		
XPP-5422GMX	<b>*</b>		<b>~</b>	<b>~</b>	<b>~</b>		
XPP-5410G	<b>*</b>		<b>~</b>	<b>~</b>	<b>~</b>	<b>~</b>	<b>*</b>
XPP-5412G	<b>*</b>		<b>*</b>	<b>~</b>	<b>*</b>		
XPP-5450G	<b>*</b>		<b>*</b>	<b>~</b>	<b>*</b>		<b>*</b>
XPP-5452G	•		<b>*</b>	<b>*</b>	<b>*</b>		
XPP-5454G	<b>*</b>		~	<b>~</b>	<b>*</b>		<b>*</b>
XPP-5456G	<b>*</b>		~	<b>~</b>	<b>*</b>	<b>~</b>	
XPP-5458G	<b>*</b>		~	<b>~</b>	<b>~</b>	<b>~</b>	
XPP-5460GX		<b>*</b>	~	<b>~</b>	<b>*</b>		
XPP-5462GX		<b>*</b>	~	<b>~</b>	<b>*</b>		
XPR-5522GMX	<b>*</b>		~	<b>~</b>	<b>~</b>	<b>~</b>	
XPR-5542GMX		<b>*</b>	~	<b>~</b>	<b>~</b>		
XPP-5450GC	<b>*</b>		~	<b>~</b>	<b>~</b>		
XPP-5452GC	<b>*</b>		~	<b>~</b>	<b>~</b>		
XPP-5454GC	<b>*</b>		~	<b>~</b>	~		<b>*</b>
XPP-5460GCX		<b>*</b>	~	<b>~</b>	~		
XPP-5466G		<b>*</b>		<b>~</b>			
XPP-5570GA		<b>*</b>	~	<b>~</b>	~	<b>~</b>	
XPR-5572GA		<b>*</b>	<b>*</b>	<b>*</b>	<b>*</b>	<b>~</b>	

Rechargeable

Limited Lifetime



640 S. Sanden Blvd. Wylie, TX 75098 (800) 233-2155 (469) 326-9400

www.nightstick.com

Nightstick products are designed in Texas, US and manufactured abroad with components from domestic and international sources.

The distinctive shapes, styles, packaging, configurations and overall appearances of these products are trademarks of Bayco Products, Inc. The unique LED configuration, body and case shapes

inherently identify them as members of the Bayco Products, Inc. portfolio.





United States Department of Labor











FLY-ISMAP-17C



# NGHTSTICK® Life Depends on Light® INTRINSICALLY SAFE LIGHTING FOR **HAZARDOUS ENVIRONMENTS**

XPR-5580G

#### **UNDERSTANDING DUAL-LIGHT™ TECHNOLOGY**

Class I Div 1 Grps A-D T3; Class II & III Div 1 Grps E-G T135°C; Class I Zone 0 AEx ia IIC T3 Ga, Class I Zone 0 Ex ia IIC T3 Ga, II 1 G Ex ia IIC T3 Ga, Ex ia IIC T3 Ga



## Flashlight

Has a focused long throw beam that is designed for distance illumination. The center spot is too bright for objects that are close-up.



#### **Floodlight**

Has a wide, even flood of light that is designed for close-up illumination. The absence of the center spot allows the user to light up areas that are close-up without the blinding bounce back of light.



## **Dual-Light**™

Combines both a long throw beam of light and a wide, even flood of light. Turning on both the flashlight and the floodlight at the same time allows the user maximum lighting versatility on the job.