

GEARWRENCH® 3 Pairs of Heavy-Duty Interchangeable Points Set

- For Heavy-Duty Snap Ring Pliers 454, 455, 456 and 2012D
- Includes 3 Pairs of Interchangeable Points and 1 Pair of Points Clamps With 2 Screws
- Requires 3/32" Hex Key When Replacing Points



Cat. No.	UPC No.	Packaging	Includes Tips Dia./ Angle	Product Weight	Shelf Pack Qty.
457	082171004575	Carded	0.108" Dia. 15°, 0.108" Dia. 45°, & 0.123" Dia. 45°	0.10 lb	1

GEARWRENCH® Combination Snap Ring Pliers

- Remove and Install Internal and External Snap Rings
- Tips Spread Up to 1-1/4"
- Tip Diameter 0.070"



Cat. No.	UPC No.	Packaging	Tip Description	Product Weight	Shelf Pack Qty.
1715D	082171017155	Carded	Tip Diameter 0.070"	0.10 lb	1

GEARWRENCH® Internal Snap Ring Pliers

- Remove and Install Internal Snap Rings From 3/8" to 1-3/4" in Diameter
- Includes 5 Pairs of Interchangeable Points
- Requires 5/64" Hex Key When Replacing Points
- Use Replacement Points Sets 447 and 448DD



Cat. No.	UPC No.	Packaging	Includes Tips Dia./ Angle	Product Weight	Shelf Pack Qty.
445	082171004452	Carded	0.039" Dia. 15° Angle; 0.048" Dia. 15° Angle; 0.074" Dia. 15° Angle; 0.039" Dia. 45° Angle; 0.047" Dia. 90° Angle;	0.35 lb	1

GEARWRENCH® External Snap Ring Pliers

- Remove and Install External Snap Rings From 1/4" to 1-7/16" in Diameter
- Includes 5 Pairs of Interchangeable Points
- Requires 5/64" Hex Key When Replacing Points
- Use Replacement Points Sets 447 and 448DD



Cat. No.	UPC No.	Packaging	Includes Tips Dia./ Angle	Product Weight	Shelf Pack Qty.
446D	082171004469	Carded	0.039" Dia. 15° Angle; 0.048" Dia. 15° Angle; 0.074" Dia. 15° Angle' 0.039" Dia. 45° Angle & 0.047" Dia. 90° Angle	0.35 lb	1