

Switches and Receptacles

GFCI Receptacles

Safety And Economy.

Switches and Receptacles

GFCI Receptacles

B7



UL Listed and CSA Certified. Meets UL943 performance requirements.

Recessed test and reset buttons to prevent accidental tripping from oversized molded plugs.

Reinforced contacts assure maximum plug retention.



Large, combination back and side wiring clamp-type terminals accept up to #10 AWG wire.

LED Indicator
Flashing red LED signals loss of GFCI protection.

Steady ON red LED signals ground fault condition.

Face and base molded of a rugged impact-resistant thermoplastic material.

Characteristics

Trip Level
Trip Time
Frequency
Voltage
Amperage
Maximum Interrupting Capacity
Operating Temperature

Maximum Humidity
Listings & Standards

Codes



Description	Rating	Color	Catalog No.		
GFCI Duplex Receptacle, Flush, Nylon Face, Back and Side Wire Terminations, Matching Nylon Wallplate Included	15A 125V NEMA 5-15R	Almond	GF15ALL		
		Black	GF15BKL		
		Brown	GF15L		
		Gray	GF15GYL		
		Ivory	GF15IL		
		Light Almond	GF15LAL		
		Red	GF15RL		
		White	GF15WL		
		GFCI Duplex Receptacle, Flush, Nylon Face, Back and Side Wire Terminations, Matching Nylon Wallplate Included	20A 125V NEMA 5-20R	Almond	GF20ALL
				Black	GF20BKL
Brown	GF20L				
Gray	GF20GYL				
Ivory	GF20IL				
Light Almond	GF20LAL				
Red	GF20RL				
White	GF20WL				
Circuit Guard Faceless GFCI, Faceless, Back and Side Wire Terminations, Matching Nylon Wallplate Included	20A 125V	Almond	GFBF20ALL		
		Black	GFBF20BKL		
		Brown	GFBF20L		
		Gray	GFBF20GYL		
		Ivory	GFBF20IL		
		Light Almond	GFBF20LAL		
		Red	GFBF20RL		
		White	GFBF20WL		
Single-Pole Switch, GFCI Grounding Receptacle, Back and Side Wire Terminations, Matching Nylon Wallplate Included	8.3A 1000W 15A 125V NEMA 5-15R	Almond	GFSP15AL		
		Black	GFSP15BK		
		Brown	GFSP15		
		Ivory	GFSP15I		
		Light Almond	GFSP15LA		
		White	GFSP15W		