

Gator® Powered 6-Ton Crimping Tools



RK425 shown with crimping jaw CJD30 (sold separately)

| CAT. NO. | UPC NO. | DESCRIPTION |
|----------|---------|---|
| RK425 | 01577 | 6-Ton Remote Crimping Tool |
| CJD3 | 03242 | Crimping Jaw with single D die groove |
| CJD3BG | 84515 | Crimping Jaw Unit - D and BG die grooves |
| CJD30 | 85414 | Crimping Jaw Unit - D and O die grooves |
| CJK | 04829 | Crimping Jaw Unit for Kearney "O" dies |
| CJB | 84513 | Cutting Jaw for one-time disposable lock hasps |
| CJXPJ | 84512 | Crimping Jaw with Nicopress X, P, & J die grooves |

Dies for use with service entrance connectors, c-taps, h-taps, overhead and underground connectors (Use with EK425L with CJD3, CJD3BG & CJD30 jaws). Use with EK425L with CJK jaws with F020735 adapters.

SPECIFICATIONS

| | |
|---------------------------|-----------------|
| Crimping Force | 6-Tons (54 kN) |
| Length (with jaws) | 15" (381 mm) |
| Width (head open) | 4" (108 mm) |
| Weight (with jaws) | 4 lbs. (1.8 kg) |
| Crimp Cycle Time | ~4 seconds |

CONNECTOR CAPACITY

| | |
|--|-------------------|
| 5/8" Service Entrance Connectors | 10-1/0 AWG |
| .840 Service Entrance Connectors | 1/0-4/0 AWG |
| Aluminum "H" Taps | 6-4/0 AWG |
| Copper "H" Taps | 10-2 AWG |
| Copper Tension Splices | 6-2/0 AWG |
| All Aluminum Tension Splices | 6-4/0 AWG |
| One Piece ACSR Tension Splices | 4-1/0 AWG |
| Two Piece ACSR Tension Splices | 2 AWG-477 kcmil |
| Aluminum Jumper Splices | 4 AWG-266.8 kcmil |
| Stirrups | 2-4/0 AWG |
| Aluminum color-coded lugs and splices | 8-4/0 AWG |

CRIMPING JAW COMPATIBILITY

| CRIMPING JAW COMPATIBILITY | BRAND | TYPE/SERIES |
|----------------------------|----------------------|--|
| CJD3BG | Greenlee® | KD6 Series |
| CJD30 | FCI Burndy® | W, X Series |
| CJD3 | IlSCO® | ND Series |
| CJK* | Huskie® | HT-58 Series |
| *Requires F020735 Adapters | Panduit® | CD-2001 Series |
| CJXPJ | Nicopress connectors | Connectors that require the X, P or J tool grooves |

CUTTING JAW COMPATIBILITY

| | |
|-----|--|
| CJB | <ul style="list-style-type: none"> • One time disposable lock hasps 4 AWG Alumoweld • ACSR 1/0 |
|-----|--|

"W"-Style dies

| CAT. NO. | UPC NO. | BURNDY NO. |
|----------|---------|------------|
| KD6-10 | 10165 | W-BG |
| KD6-11 | 10166 | W-O |
| KD6-12 | 10167 | W-C |
| KD6-13 | 10168 | W-K840 |
| KD6-14 | 10169 | W-161 |
| KD6-15 | 10170 | W-162 |
| KD6-16 | 10171 | W-163 |
| KD6-17 | 10172 | W-165 |
| KD6-18 | 10173 | W-166 |
| KD6-19 | 10174 | W-243 |
| KD6-20 | 10175 | W-247 |
| KD6-21 | 10176 | W-249 |
| KD6-22 | 10177 | W-164 |
| KD6-24 | 10179 | W-237 |
| KD6-25 | 10180 | W-239 |
| KD6-27 | 10182 | W-28K |

The products listed above are registered trademarks of Anderson®, Blackburn®, FCI Burndy®, ILSCO®, Panduit®, Penn-Union® and Thomas & Betts®.



CJD3BG



CJD30



CJD3



CJK



CJB



CJXPJ