# Single-Flute and Three-Flute Countersink Styles 209SF and 213

# Features/Benefits:

- Designed to countersink, chamfer, deburr, and enlarge holes in sheet metal.
- Use single flute countersinks in holes too small for multi-flute countersinks. Use multi-flute countersinks in much larger size holes.
- Manufactured from premium high-speed steel.
- $\bullet$  Single-flute available with 82° and 90° point angles; three-flute available with  $82^{\circ}$ ,  $90^{\circ}$  and  $100^{\circ}$  point angles.
- Black finish with bright point.

# **Application Information:**


- tool steel
- allov steel
- cast iron
- Recommended for portable applications and machine work.
- Operate at high speeds and light feeds for best results.

#### **Surface Treatment Information:**

• Black oxide surface finish increases wear resistance and adds lubricity. improving chip flow.







# STYLE 209SF SINGLE-FLUTE — INCH SIZES

Diameter			Shank	Shank Diameter		Length	Style 2	Style 209SF	
Fract	Decimal	mm	inch	mm	inch	mm	82° Angle	90° Angle	
1/4	.2500	6.35	.1875	4.76	1.5000	38.10	56736	56756	
3/8	.3750	9.53	.2500	6.35	1.7500	44.45	56738	56758	
1/2	.5000	12.70	.2500	6.35	2.0000	50.80	56740	56760	
3/4	.7500	19.05	.5000	12.70	2.6250	66.68	56744	56774	
1	1.0000	25.40	.5000	12.70	2.7500	69.85	56748	56778	

## STYLE 213 THREE-FLUTE — INCH SIZES

Diameter		Shank D	Shank Diameter		Overall Length		Shank Length		Style 213		
Fract	Decimal	mm	inch	mm	inch	mm	inch	mm	82° Angle	90° Angle	100° Angle
1/4	.2500	6.35	.1875	4.76	1.5000	38.10	.7500	19.05	56836	56856	56876
3/8	.3750	9.53	.2500	6.35	1.7500	44.45	.8750	22.23	56838	56858	56878
1/2	.5000	12.70	.2500	6.35	2.0000	50.80	1.0000	25.40	56839	56859	56879
1/2	.5000	12.70	.3750	9.53	2.0000	50.80	1.0000	25.40	56840	56860	56880
5/8	.6250	15.88	.3750	9.53	2.2500	57.15	1.0000	25.40	56842	56862	56882
3/4	.7500	19.05	.5000	12.70	2.6250	66.68	1.2500	31.75	56844	56864	56884

### **INCH SET**

		Case	Style 213
Number of Tools	Size Range	Style	82° Angle
5	1/4 - 3/4 X 1/8	plastic pouch	64216



Technical Support: 800.892.4281

Set 64216

