Taps • Pipe

List #s962B NPT, 970B NPTF Low Hook Taper Pipe Tap







Substrate - High Speed Steel
Surface Treatment - Bright
Chamfer - 3-1/2 threads
Cut Type - Pipe



Features:

- Low Hook for tool strength
- Ground threads for better surface finish & tighter tolerances
- Small shank available 1/8"
- NPT/NPTF thread design

| Diameter | Decimal Equivalent | Threads Per Inch | Number Of Flutes | Shank Diameter | Overall Length | Thread Length | 962B NPT • EDP I | 970B NPTF Number • |
|----------|-----------------------|---------------------|---------------------|-------------------|-------------------|------------------|------------------------|--------------------------|
| 1/6 | .0625 | 27 | 4 | .3125 | 2-1/8 | 11/16 | C64003 | C64025 |
| 1/8* | .1250 | 27 | 4 | .3125 | 2-1/8 | 3/4 | C64004 | C64026 |
| 1/8 | .1250 | 27 | 4 | .4375 | 2-1/8 | 3/4 | C64005 | C64027 |
| 1/4 | .2500 | 18 | 4 | .5625 | 2-7/16 | 1-1/16 | C64006 | C64028 |
| 3/8 | .3750 | 18 | 4 | .7000 | 2-9/16 | 1-1/16 | C64007 | C64029 |
| 1/2 | .5000 | 14 | 4 | .6875 | 3-1/8 | I-3/8 | C64008 | C64030 |
| 3/4 | .7500 | 14 | 5 | .9063 | 3-1/4 | I-3/8 | C64009 | C64031 |
| l | 1.0000 | 11-1/2 | 5 | 1.1250 | 3-3/4 | I-3/4 | C64010 | C64032 |
| 1-1/4 | 1.2500 | 11-1/2 | 5 | 1.3125 | 4 | I-3/4 | C64011 | C64033 |
| I-I/2 | 1.5000 | 11-1/2 | 7 | 1.5000 | 4-1/4 | I-3/4 | C64012 | C64034 |
| 2 | 2.0000 | 11-1/2 | 7 | 1.8750 | 4-1/2 | I-3/4 | C64013 | C64035 |

^{*} Small Shank

List #s965B NPT, 975 NPTF, 975TN NPTF

Medium Hook Taper Pipe Tap





Substrate - High Speed Steel
Surface Treatment - Bright/TiN
Chamfer - 3-1/2 threads
Cut Type - Pipe



Features:

- Medium hook for general purpose
- Ground threads for better surface finish & tighter tolerances
- Small shank available 1/8"
- NPT/NPTF thread design
- TiN coated for higher speeds & wear resistance

| Diameter | Decimal Equivalent | Threads Per Inch | Number Of Flutes | Shank Diameter | Overall Length | Thread Length | 965B NPT Bright | 975 NPTF Bright • EDP Number | 975TN NPTF TiN |
|----------|-----------------------|---------------------|---------------------|-------------------|-------------------|------------------|-----------------------|---------------------------------------|----------------------|
| 1/6 | .0625 | 27 | 4 | .3125 | 2-1/8 | 11/16 | C64036 | C64058 | C55680 |
| 1/8* | .1250 | 27 | 4 | .3125 | 2-1/8 | 3/4 | C64037 | C64059 | |
| 1/8 | .1250 | 27 | 4 | .4375 | 2-1/8 | 3/4 | C64038 | C64060 | C55682 |
| 1/4 | .2500 | 18 | 4 | .5625 | 2-7/16 | 1-1/16 | C64039 | C64061 | C55683 |
| 3/8 | .3750 | 18 | 4 | .7000 | 2-9/16 | 1-1/16 | C64040 | C64062 | C55684 |
| 1/2 | .5000 | 14 | 4 | .6875 | 3-1/8 | I-3/8 | C64041 | C64063 | C55685 |
| 3/4 | .7500 | 14 | 5 | .9063 | 3-1/4 | I-3/8 | C64042 | C64064 | C55686 |
| I | 1.0000 | 11-1/2 | 5 | 1.1250 | 3-3/4 | I-3/4 | C64043 | C64065 | C55687 |
| I-I/4 | 1.2500 | 11-1/2 | 5 | 1.3125 | 4 | I-3/4 | C64044 | C64066 | |
| 1-1/2 | 1.5000 | 11-1/2 | 7 | 1.5000 | 4-1/4 | I-3/4 | C64045 | C64067 | |
| 2 | 2.0000 | 11-1/2 | 7 | 1.8750 | 4-1/2 | I-3/4 | C64046 | C64068 | |

^{*} Small Shank

