

Drills • MRO

List # 1820 Cle-Line® Taper Length Drill - Surface Treated



Substrate - HSS
 Length - Taper Length
 Surface Treatment - Black Oxide
 Shank - Straight with Tang
 Point - 118°



Features:

- HSS engineered for toughness & ideal for portable drilling & maintenance applications
- Taper length for extended reach
- Black oxide finish for increased wear resistance & improved lubricity, reducing chip welding & galling
- Tanged shank for use with ASA drill drivers
- Heavy duty construction for extra tool strength

Diameter	Decimal Equiv.	Metric Equiv.	Overall Length	Flute Length	EDP Number
1/16	.0625	1.59	3	1-3/4	C10260
5/64	.0781	1.98	3-3/4	2	C10261
3/32	.0938	2.38	4-1/4	2-1/4	C10262
7/64	.1094	2.78	4-5/8	2-1/2	C10263
1/8	.1250	3.18	5-1/8	2-3/4	C10264
9/64	.1406	3.57	5-3/8	3	C10265
5/32	.1562	3.97	5-3/8	3	C10266
11/64	.1719	4.37	5-3/4	3-3/8	C10267
3/16	.1875	4.76	5-3/4	3-3/8	C10268
8	.1990	5.05	6	3-5/8	C10269
13/64	.2031	5.16	6	3-5/8	C10270
7/32	.2188	5.56	6	3-5/8	C10271
15/64	.2344	5.95	6-1/8	3-3/4	C10272
1/4	.2500	6.35	6-1/8	3-3/4	C10273
17/64	.2656	6.75	6-1/4	3-7/8	C10274
6.80mm	.2677	6.80	159mm	98mm	C10275

Diameter	Decimal Equiv.	Metric Equiv.	Overall Length	Flute Length	EDP Number
9/32	.2812	7.14	6-1/4	3-7/8	C10276
19/64	.2969	7.54	6-3/8	4	C10277
5/16	.3125	7.94	6-3/8	4	C10278
21/64	.3281	8.33	6-1/2	4-1/8	C10279
R	.3390	8.61	6-1/2	4-1/8	C10280
11/32	.3438	8.73	6-1/2	4-1/8	C10281
23/64	.3594	9.13	6-3/4	4-1/4	C10282
3/8	.3750	9.53	6-3/4	4-1/4	C10283
25/64	.3906	9.92	7	4-3/8	C10284
13/32	.4062	10.32	7	4-3/8	C10285
27/64	.4219	10.72	7-1/4	4-5/8	C10286
7/16	.4375	11.11	7-1/4	4-5/8	C10287
29/64	.4531	11.51	7-1/2	4-3/4	C10288
15/32	.4688	11.91	7-1/2	4-3/4	C10289
31/64	.4844	12.30	7-3/4	4-3/4	C10290
1/2	.5000	12.70	7-3/4	4-3/4	C10291

List # 1840 Cle-Line® Taper Length Drill - Surface Treated - Taper Shank



Substrate - HSS
 Length - Taper Shank Length
 Surface Treatment - Black Oxide
 Shank - Taper with Tang
 Point - 118°



Features:

- HSS steel engineered for toughness & ideal for portable drilling & maintenance applications
- 118° point for general purpose use
- Black oxide finish for increased wear resistance & improved lubricity, reducing chip welding & galling

Diameter	Decimal Equiv.	Metric Equiv.	Overall Length	Flute Length	Pipe Thread Size	EDP Number
3/8	.3750	9.53	6-3/4	3-1/2	1	C09900
25/64	.3906	9.92	7	3-5/8	1	C09901
13/32	.4062	10.32	7	3-5/8	1	C09902
27/64	.4219	10.72	7-1/4	3-7/8	1	C09903
7/16	.4375	11.11	7-1/4	3-7/8	1	C09904
29/64	.4531	11.51	7-1/2	4-1/8	1	C09905
15/32	.4688	11.91	7-1/2	4-1/8	1	C09906
31/64	.4844	12.30	8-1/4	4-3/8	2	C09907
1/2	.5000	12.70	8-1/4	4-3/8	2	C09908
33/64	.5156	13.10	8-1/2	4-5/8	2	C09909
17/32	.5312	13.49	8-1/2	4-5/8	2	C09910
35/64	.5469	13.89	8-3/4	4-7/8	2	C09911
9/16	.5625	14.29	8-3/4	4-7/8	2	C09912
37/64	.5781	14.68	8-3/4	4-7/8	2	C09913
19/32	.5938	15.08	8-3/4	4-7/8	2	C09914
39/64	.6094	15.48	8-3/4	4-7/8	2	C09915
5/8	.6250	15.88	8-3/4	4-7/8	2	C09916

Diameter	Decimal Equiv.	Metric Equiv.	Overall Length	Flute Length	Pipe Thread Size	EDP Number
41/64	.6406	16.27	9	5-1/8	2	C09917
21/32	.6562	16.67	9	5-1/8	2	C09918
43/64	.6719	17.07	9-1/4	5-3/8	2	C09919
11/16	.6875	17.46	9-1/4	5-3/8	2	C09920
45/64	.7031	17.86	9-1/2	5-5/8	2	C09921
23/32	.7188	18.26	9-1/2	5-5/8	2	C09922
47/64	.7344	18.65	9-3/4	5-7/8	2	C09923
3/4	.7500	19.05	9-3/4	5-7/8	2	C09924
49/64	.7656	19.45	9-7/8	6	2	C09925
25/32	.7812	19.84	9-7/8	6	2	C09926
51/64	.7969	20.24	10-3/4	6-1/8	3	C09927
13/16	.8125	20.64	10-3/4	6-1/8	3	C09928
53/64	.8281	21.03	10-3/4	6-1/8	3	C09929
27/32	.8438	21.43	10-3/4	6-1/8	3	C09930
55/64	.8594	21.83	10-3/4	6-1/8	3	C09931
7/8	.8750	22.23	10-3/4	6-1/8	3	C09932
57/64	.8906	22.62	10-3/4	6-1/8	3	C09933

(Continued on next page)