

Other Drills Masonry

Fast Helix Carbide-Tipped Masonry

FEATURES

- Oversize carbide tip provides clearance for toggle bolts, anchor screws and expansion drills
- Fast helix for higher volume material removal
- For use in hard concrete
- Available in regular lengths and extended lengths
- Conforms to ANSI specification B212.15-1994
- Recommended for use in aggregate and hard concrete



Style 1889 Regular Length Bright



Style 1888 12" Overall Length Bright



Style 1888 18" Overall Length Bright

INCH SIZES

Drill Dia.	Minimum Actual Dia.	Metric Equiv.	Shank Dia.	Overall Length	Useable Length	Style 1889 Regular OAL Bright
1/8	.134	3.40	1/8	3	1-1/4	C23286
3/16	.198	5.03	3/16	4	1-3/4	C23270
1/4	.260	6.60	1/4	4	2-1/2	C23287
1/4	.260	6.60	1/4	6	4-1/2	C23271
1/4	.260	6.60	1/4	12	9-1/2	C23272
5/16	.327	8.31	1/4	4	2-1/2	C23288
5/16	.327	8.31	1/4	6	4-1/2	C23273
5/16	.327	8.31	1/4	12	9-1/2	C23274
3/8	.390	9.91	1/4	4	2-1/2	C23289
3/8	.390	9.91	1/4	6	4-1/2	C23275
3/8	.390	9.91	1/4	12	9-1/2	C23276
7/16	.428	10.87	1/4	4	4-3/8	C22539
7/16	.428	10.87	1/4	6	4-3/8	C23277
1/2	.520	13.21	1/4	4	4-3/8	C23278
1/2	.520	13.21	1/4	6	4-3/8	C23279
1/2	.520	13.21	3/8	6	4-3/8	C23280
1/2	.520	13.21	3/8	12	9-1/2	C23281
9/16	.582	14.78	3/8	6	4-3/8	C22540
5/8	.650	16.51	3/8	6	4-3/8	C23282
3/4	.775	19.69	3/8	6	4-3/8	C23283
7/8	.905	22.99	1/2	6	4-3/8	C23284
1	1.030	26.16	1/2	6	4-3/8	C23285

EXTENDED LENGTH INCH SIZES

Drill Dia.	Minimum Actual Dia.	Metric Equiv.	Shank Dia.	Style 1888	
				9-3/4" Useable Length 12" OAL	15-3/4" Useable Length 18" OAL
1/4	.260	6.60	1/4	C20970	C20960
5/16	.328	8.33	1/4	C20971	C20961
3/8	.390	9.91	1/4	C20972	C20962
1/2	.525	13.34	3/8	C20973	C20963
5/8	.650	16.51	1/2	C20974	C20964
3/4	.775	19.69	1/2	C20975	C20965
7/8	.905	22.99	1/2	C20976	—
1	1.030	26.16	1/2	C20977	C20966

SETS IN PLASTIC CASE

Drill Sizes	No. of Pieces	Overall Length	Style 1889 Bright
1/4", 5/16", 3/8", 1/2"	4	4	C23290



Customer Service: 800.348.2885

DRILLS

HOLE SAWS

TAPS & DIES

BURS

INDEX

Other Drills Masonry

Rotary Percussion Carbide-Tipped Masonry

FEATURES

- 130° point
- Perfect for high impact drilling
- Can be used in hard marble, fieldstone, granite and concrete
- Specifically designed for use in heavy duty hammer drills
- Conforms to ANSI specification B212.15-194



Style 1819 Black Oxide

INCH SIZES

Drill Dia.	Minimum Actual Dia.	Metric Equiv.	Overall Length	Flute Length	Shank Diameter	Style 1819 Black Oxide
1/8	.134	3.40	3	1-5/8	1/8	C20700
5/32	.165	4.19	6	3-1/8	5/32	C20701
3/16	.198	5.03	4	2-1/2	3/16	C20702
3/16	.198	5.03	6	2-1/2	3/16	C20703
1/4	.260	6.60	6	3-1/4	1/4	C20704
1/4	.260	6.60	12	9-1/8	1/4	C20705
5/16	.327	8.31	6	3-1/2	1/4	C20706
3/8	.390	9.91	6	3-3/4	1/4	C20707
1/2	.520	13.21	6	4	3/8	C20708
1/2	.520	13.21	12	9-1/2	1/2	C20709
5/8	.650	16.51	6	3-5/8	3/8	C20710
3/4	.775	19.69	6	3-1/2	1/2	C20711

Tanged Tapcon® Carbide-Tipped Masonry

FEATURES

- For use with Tapcon® type anchoring systems
- Hardened alloy steel for long life and superior performance
- Close tolerance carbide tip



Style 1841 Black Oxide

Drill Dia.	Decimal Equiv.	Metric Equiv.	Overall Length	Useable Length	Style 1841 Black Oxide
5/32	.1562	3.97	4-1/2	3-1/2	C19010
5/32	.1562	3.97	5-1/2	4-1/2	C19012
3/16	.1875	4.76	4-1/2	3-1/2	C19011
3/16	.1875	4.76	5-1/2	4-1/2	C19013



Customer Service: 800.348.2885

DRILLS

HOLE SAWS

TAPS & DIES

BURS

INDEX