

EDP NUMBER	CAT. NUMBER	DESCRIPTION	F.L. AMPS	SHIP WT.	LIST	
MOTORS						
21021	967J	Single-phase, three speed, 115 volt, 1/5 HP, ball bearing, oscillating, 5/8" shaft (use only on standard 18" and 20" oscillating fans). Use BA-1A Propeller NOTE: Oscillating Motor NOT to be used in UPSIDE-DOWN position (1)	1.65	24	\$526	
21007	967-3 SP.	Single-phase, three speed, 115 volt, 1/3 HP, ball bearing, oscillating, 5/8" shaft (use only on standard 24" and 30" oscillating fans). Use BA-1A Propeller NOTE: Oscillating Motor NOT to be used in UPSIDE-DOWN position (1)	2.7	23	\$751	
21777		Gear box assembly for 967J and 967-3SP			\$174	
03915		End dome assembly for 967J and 967-3SP (includes capacitor)			\$62	
21022	642J	Single-phase, three speed, 115 volt, 1/5 HP, ball bearing, non-oscillating, 5/8" shaft (use only on standard 18" and 20" non-oscillating fans). Use BA-1A Propeller (2)	1.65	18	\$264	
21017	642-AC 3 SP.	Single-phase, three speed, 115 volt, 1/3 HP, ball bearing, non-oscillating, 5/8" shaft (use only on standard 24" and 30" non-oscillating fans). Use BA-1A Propeller (2)	2.8	19	\$378	
06004		End dome assembly for 642J and 642-AC-3SP (includes capacitor)			\$49	
21090	642-AC2SDP	Single phase, 2-speed, 115 volt, 1/3 HP, ball bearing, non-oscillating motor with 2-speed drop cord switch. Use with BA-1A propeller (3)		19	\$397	
12013	2-SPDCS-HD	Modular end dome with drop cord and 2 speed switch. For 642 Motor Only. (4)		2	\$82	
21025	1069 B*	Three-phase, 1 Sp., 230/460 volt, 1/4 HP, ball bearing, use only on non-oscillating fans. Use BA-1A Propeller (5)	1.2/1.6	16	\$731	
21035	1169 E*	Single-phase, single-speed, 115/230 volt, 1/4 HP, ball bearing for Class.I Group D and Class.II, Groups E, F & G. (Use only on explosion-proof, non-oscillating fans with BA-1A Propeller). (6)	6.9/3.5	48	\$889	
21040	1269*	Three-phase, single-speed, 230/460 volt, 1/4 HP, ball bearing (use only on non-oscillating, explosion-proof fans). Use BA-1A Propeller, Class I Group D, Class II, Groups E, F & G. (7)	1.1/1.55	33	\$1085	
21050	1369*	1 HP, three-phase, single-speed 208-230/460 volt, ball bearing, totally enclosed (use only on high-velocity spot coolers). Use HH-1 Propeller (8)	4.0/2.0	36	\$946	
*Explosion proof and 3 phase air circulator motors are not supplied with switches or power cords.						
GUARDS						
71000	C-1820G	18" / 20" guard (use on all 18" and 20" oscillating & non-oscillating fans). Nickel Chrome Plated.		11	\$ 89	
21070	AC24-G	24" guard (use on all 24" oscillating & non-oscillating fans) Nickel Chrome Plated.		14	\$110	
21080	AC30-G	30" guard (use on all 30" oscillating & non-oscillating fans) Nickel Chrome Plated.		20	\$162	
21082	AC30GS	30" Bolt fastened safety guard (pat. no. 4,861,230) Zinc.		18	\$195	
70761	AC30GSS	30" Stainless steel guard		18	\$547	
PROPELLERS						
21101	18BA-1	18" Propeller - 5/8" bore. Cast Aluminum.		4	\$149	
21102	20BA-1	20" Propeller - 5/8" bore. Cast Aluminum.		5	\$159	
21095	24BA-1A	24" Propeller - 5/8" bore. Cast Aluminum.		5	\$176	
21105	30BA-1A	30" Propeller - 5/8" bore. Cast Aluminum.		6	\$186	
21120	24HH-1	24" Propeller, 5/8" bore (use only on 24" high velocity spot coolers.) Galvanized.		8	\$76	
21130	30HH-1	30" Propeller, 5/8" bore (use only on 30" high velocity spot coolers.) Galvanized.		9	\$89	
PEDESTAL (Adjustable)						
21152	8CP-2B	5' to 8' pedestal (fits all Heavy Duty fans.)		13	\$95	
FLOOR BASE						
21165	A786B-1	For use with 18" and 20" oscillating & non-oscillating fans with 8CP-2B pedestal.		17	\$88	
21166	A786B-2	For use with 24" and 30" oscillating & non-oscillating fans with 8CP-2B pedestal.		34	\$90	
WALL BRACKET (15° Tilt Built In)						
21187	878W	Use for HD air circulator wall mountings. Includes Safety Cable Kit.		10	\$99	
I-BEAM BRACKET						
21191	700-U	Use for HD air circulator I-Beam mountings. Includes Safety Cable Kit.		14	\$162	
CEILING BRACKET						
21203	CK-2	Use for HD air circulator ceiling mount (non-oscillating only). Extension pipe not included. Includes Safety Cable Kit.		5	\$71	
ACCESSORIES						
21204	Safety Kit	12' of 1/16" diameter cable, two clamp and instructions. This safety cable kit is available for retrofit applications.		1	\$23	
12002	DJ-EC-6	6' extension cord - for use with 642-AC2SDP Drop Cord Motor - Yellow		1	\$21	
12008	DJ-EC-9	9' extension cord - for use with 642-AC2SDP Drop Cord Motor - Yellow		2	\$22	
12009	DJ-EC-12	12' extension cord - for use with 642-AC2SDP Drop Cord Motor - Yellow		2	\$24	
70601	AMFW30K	Snap on wheel kit with set screw lock for use on all floor model air circulators except I-2030 base. No tools required.		7	\$63	
01633		15' Cord Replacement		2	\$24	
01723		2SP/3SP Pull Chain Switch		2	\$14	

NOTES:
Explosion Proof and 3 Phase air circulator motors are not supplied with switches or power cords. Must be hard wired.
See page 43 for further Explosion Proof Motor information.

