

# H3000D

**EXTRA ABRASION RESISTANT FRAS**  
**ISOBARIC SPIRAL HOSE**  
**215 BAR / 3100 PSI**  
**MILLION CYCLE**



INTRODUCTION

HOSE

COUPLINGS

ADAPTORS

TECHNICAL

**RECOMMENDED FOR:**

High pressure hydraulic oil lines. Constant pressure (Isobaric) 215 bar / 3100 psi in all sizes. Small bend radius is an advantage in installations.

**PERFORMANCE:**

Meets or Exceeds the Performance Requirements of: EN 856 Type R12, EN 856 Type 4SP, ISO 18752-DC, SAE 100R12.

**TUBE:**

Black, oil resistant synthetic rubber.

**REINFORCEMENT:**

Four alternating layers of spiralled high tensile steel wire.

**COVER:**

**DIEHARD™** Black, oil and extra abrasion resistant synthetic rubber. Flame Resistant, Anti-Static (FRAS) & MSHA compliant. Highly visible layline branding for easy and permanent identification. No skiving required with T7000 Series Crimp Couplings.

**FEATURES:**

Tested to **1 million impulse cycles** at up to 1/2 SAE 100R12 Minimum Bend Radius. Constant pressure 215 bar / 3100 psi in all sizes for easy system design and hose selection. Small bend radius is an advantage in installations.

**FRAS - FLAME RESISTANCE AND ANTI-STATIC:**

**DIEHARD™** complies with Flame Resistant and Electrical Resistance (Anti-Static) requirements of Australian Standard AS 2660 and Methods of Test AS 1180.10B and 13A. Meets Flame Resistant Designation "U.S. MSHA" of the US Department of Labor, Mine Safety and Health Administration.

**TEMPERATURE RANGE:**

-40°C to +121°C (-40°F to +250°F).  
 For water, emulsions etc. see page 58.

**WORKING PRESSURE:**

Maximum working pressures are based on 4:1 safety factor (maximum working pressure to minimum burst pressure).

**THIRD PARTY APPROVALS:**

ABS, DNV-GL, LR, MED, USCG, GOST-R, BV, RINA and KR.

**COUPLINGS:**

**NON-SKIVE ONE-PIECE CRIMP**  
**T2000 Series** (sizes -20 to -32) pages 187 to 232. Assembly Instructions pages 478.

H3000D - DIEHARD ISOBARIC SPIRAL HOSE															
PART NO	HOSE SIZE	NOMINAL HOSE ID		NOMINAL HOSE OD		MAXIMUM WORKING PRESSURE		MINIMUM BURST PRESSURE		MINIMUM BEND RADIUS		AVERAGE WEIGHT		COUPLING SERIES ONE PIECE	
Hose	DN	Dash	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	NON-SKIVE
H3020D	31	-20	31,8	1.1/4	45,7	1.80	215	3100	860	12400	200	7.9	2,27	1.53	T7000
H3024D	38	-24	38,1	1.1/2	50,3	1.98	215	3100	860	12400	250	9.8	2,35	1.58	T7000
H3032D	51	-32	50,8	2	63,3	2.49	215	3100	860	12400	400	15.8	3,40	2.28	T7000

Refer to the latest RYCO Crimp Charts for crimp diameter and mark lengths.